



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



MiniTec[®] Digital MultiMeters

Rugged pocket design with 8 to 11 Functions

Includes Relative zero, Data Hold and Range Hold

- 4000 counts on large LCD with full function indication
- Measures AC/DC Voltage and Current, Resistance, Capacitance, Frequency and Temperature
- Temperature measurements to 1400°F (760°C)
- Duty Cycle, Continuity and Diode test
- Autoranging with manual range override
- 10A fuse protection
- Overload protection and indication
- Auto power off saves battery life
- Includes protective rubber holster, general purpose bead wire Type K temperature probe (Model MN26T), two 1.5V AAA batteries and test leads



MN26T

MN25



Test Leads included for easy measurements

Specifications	MN25	MN26T	Basic Accuracy	
	(Manual Ranging)	(Autoranging)	(MN25/MN26T)	
Display Count	2000 count	4000 count		
DC Voltage	600V (0.1mV)	600V (0.1mV)	±0.5%	±1.0%
AC Voltage	600V (0.1V)	600V (0.1mV)	±1.5%	±1.5%
DC Current	10A (1µA)	10A (0.1µA)	±1.2%	±1.5%
AC Current	10A (1µA)	10A (0.1µA)	±1.8%	±1.8%
Resistance	2MΩ (0.1Ω)	40MΩ (0.1Ω)	±0.8%	±1.2%
Capacitance	—	200µF (0.001nF)	—	±3.5%
Frequency	—	10MHz (0.001Hz)	—	±1.5%
Temperature	—	0 to 1400°F (1°) 0 to 760°C (1°)	—	±3.0%
Duty Cycle	—	0.1% to 99.9% (0.1%)	—	±1.2%
Diode/Continuity	Yes	Yes		
Dimensions/ Wt	4.8x2.4x1.6" (122x61x40mm)/ 9.17oz (260g)			

Ordering Information:

MN25Manual Ranging MiniTec[®] Digital MultiMeter

MN26TAuto Ranging MiniTec[®] Digital MultiMeter

TP873Spare Type K Bead Wire Temperature Probe (-22 to 572°F/-30 to 300°C)

409992Vinyl Pouch Carrying Case

