imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



		8	7	6	5	4	3
_	D		58.84MM		NGTH (Mxxx=Meters) (Exxx=Feet)		2.39MM
	С		3 FACE VIEW	P1 1 2 3 	P2 GREEN BLACK WHITE	1 2 3 2 FACE VIEW	
_	В	INSULATION CONTACT: GO OVERMOLD M CABLE RATIN CABLE JACKI CONDUCTOR NUMBER OF 2) ELECTRICAL DA CURRENT (M VOLTAGE (M) INSULATION	ET MATERIAL: PVC COLOR: YI R INSULATION: PVC CONDUCTORS: (3) 16AWG TA:	94/V-0 PPER ALLOY COLOR: YELLOW SA CERTIFIED TYPE ST, FT2 FL ELLOW	AME RATING, 600V, 105°C.		
	A	PROTECTION MATING CYC VIBRATION R THERMO SHO	RE RANGE: -20°C TO +105°C I: IP67 (MATED CONDITION) LES: >500 ESISTANCE PER MIL-STD-202 I DCK PER MIL-STD-202 METHOE T SPRAY PER MIL-STD-202 ME IT ASSEMBLY	207	3- 9-1	8.99 M = +150.0/-25.0mm 10.00 4.99 M = +300.0/-25.0mm 30.00	1.99 FT = +4" / -1" -29.99 FT = +6" / -1" 49.99 FT = +12" / -1" FOVER = +18" / -1"
		8	7	6	5	4	3

				2						1				
						REVISIC								
╞	A1	ZONE	ECO	TECHNICAL		SCRIPT ET RELEASE				DATE 07-CCT-15	BY JLAG	CHK	APPR -	
			I											
														D
														С
														TTLE: WINI, 3 PIN, M-1
														ani, 3 pin, M-Str, F-Str, Meters
					/G	Do I Ri	Not I sque	Discon e de ch lebranc	nect L ocs el cher se	Shock Inder Load lectriques ous tensic				DWG NO: MN37A4ACO1MXXX
			PART						SCRIF	PTION	1		ITEM	REV: B2 SH
	1) All dim 2) Tolerar 1 PL DE 2 PL DE	OTHERN ensions a nces are a C ±0.30 C ±0.15	VISE SPECIFIED re in metric(mm). s follows: Fractions ±1/64 Angles ±1°	DRAWN:	NATURES	12-MAY-14	<u> </u>			ph				-1 99
	3 PL DE 3) Note re MATERIAL	C ±0.08	- 🖄	ENGINEER: APPROVAL: CUSTOMER:	MRF KMM RFC	12-MAY-14 12-MAY-14		STRAIG	44724 Clinton SS M22 HT TO	vstems - www.s Morley Drive Township, MI (7/8"), 3 PII FEMALE, S	48036 N, MALE			
	PROCESS NEXT ASS'		IONS:	INFORMATIO SPECIFICATIO SHOWN HERI THE AMPHEN OF REPRODU DIMENSIONS	IG IS SUPPLIED N ONLY. DESIGI ONS AND PERF EON ARE THE P IOL CORPORAT JCTION ARE IMF ARE SUBJECT RING VARIATIOI	N FEATURES, DRMANCE DATA ROPERTY OF ION. NO RIGHTS PLIED. ALL TO NORMAL	SIZE	STOOW,	DWG NO:	MN37A			A1	
	I			2				HALF		37A4AC01 1	IVI	1 •	F 1]