



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## 3M™ Dual Lock™ Reclosable Fastener MP3550

3M ID 70006765104, 3M Product Number MP3550, UPC 00051115817427



- A black fastener with mushroom shaped stems backed with a white general purpose acrylic pressure sensitive adhesive.
- Type 250 stem density polyolefin fastener which mates to Type 250 or 400.
- Designed to bond to metals, glass and medium to high surface energy plastics and paint.

## Specifications

Attribute Name	Value
Color	Black
Length	60.14 Linear Yard
Length (Metric)	55 m
Product Form	Pack
Volatile Organic Compounds (VOCs)	See Safety Data Sheet, Regulatory Data Sheet
Width	0.236 Inch
Width (Metric)	6 mm

## Details

- A black fastener with mushroom shaped stems backed with a white general purpose acrylic pressure sensitive adhesive.
- Type 250 stem density polyolefin fastener which mates to Type 250 or 400.
- Designed to bond to metals, glass and medium to high surface energy plastics and paint.

A general purpose, acrylic adhesive on the back of a black polypropylene reclosable fastener. 250 stems per square inch. .22 engaged thickness. Closure life 1000.

For indoor and outdoor use High temperature performance, temperature resistance 200 degrees F For use with metals (aluminum stainless steel), glass, medium to high surface energy plastics (acrylic polycarbonate, ABS) and paints.