



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## VRLA Rechargeable Battery

# MPL155-12



### FEATURES

- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Low self-discharge rate,lower than 3% capacity loss per month
- Can be used in any orientation(excluding used inverted)
- The battery is designed with very lower resistance and exceeding high power performance
- Flame-arrestor is installed to ensure safety
- Absorbent Glass Mat technology for efficient gas recombination

### APPLICATION

- UPS
- Telecom
- Golf-Carts
- Cable TV
- Power station
- Marine



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	150.0Ah @ 10 hour rate F.V.(1.75V/cell)
Approx. Weight	45.5Kg(100.3lbs.)
Terminals	I3
Internal Resistance	≤2.7mΩ (Fully Charged )
Max. Charge Current	45.0 A
Short Circuit Current	3850 A
Operating Temperature Range	Charge : 0°C~50°C(32°F~122°F) Discharge : -20°C~60°C(-4°F~140°F) Storage. : -20°C~50°C(-4°F~122°F)
Container Material	Standard: PP( UL 94-HB) MPL155-12 Optional: Flame Retardant PP(UL 94-V0) MPL155-12FR



- IEC60896-21/22
- JIS C 8704-2
- GB/T 19638.2

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> <li>■ Length 344±2.0 (13.54±0.08)</li> <li>■ Width 173±2.0 (6.81±0.08)</li> <li>■ Container Height 270.5±2.0 (10.65±0.08)</li> <li>■ Total Height 277±2.0 (10.91±0.08)</li> </ul>		<ul style="list-style-type: none"> <li>● Terminal I3</li> <li>16.0</li> <li>M8x1.25</li> <li>2.5</li> </ul> <p>Terminal Hardware Initial Torque: I3(10.0Nm±5%)</p>

Constant power discharge characteristics at 25 °C/77 °F Unit: W										
Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
1.80V	4746	3981	3277	2740	2375	2086	1679	1409	1221.1	868.0
1.75V	5196	4226	3467	2847	2446	2139	1714	1438	1240.0	881.8
1.70V	5612	4400	3586	2921	2494	2173	1738	1455	1253.8	892.1
1.65V	5994	4536	3667	2976	2533	2198	1758	1471	1265.8	899.0
1.60V	6150	4623	3720	3016	2564	2218	1776	1483	1276.2	904.2

Constant current discharge characteristics at 25 °C/77 °F Unit: A										
Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	20 Min	25 Min	30 Min	40 Min	50 Min	60 Min	90 Min
1.80V	430	350	284	234	200	174	140	117	102.6	72.9
1.75V	473	375	300	245	208	181	143	121	104.2	74.1
1.70V	516	401	310	251	214	184	146	122	105.4	74.9
1.65V	565	424	319	257	217	188	148	124	106.4	75.6
1.60V	598	446	324	260	220	189	150	126	107.1	76.1

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained herein.