



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Surface Mount 30,000 Watt Transient Voltage Suppressor

High-Reliability  
screening available in  
reference to  
MIL-PRF-19500

### DESCRIPTION

These high power 30 kW rated transient voltage suppressors in a surface mount package are provided with design features to minimize thermal resistance and cumulative heating. Typical applications include lightning and automotive load dump protection. They are particularly effective at meeting the multi-stroke lightning standard RTCA DO-160, section 22 for aircraft design. This efficient low profile package design is offered in standoff voltage selections ( $V_{WM}$ ) of 14 volts to 400 volts in either unidirectional or bidirectional construction.

**Important:** For the latest information, visit our website <http://www.microsemi.com>.


### FEATURES

- Available in both unidirectional and bidirectional construction (bidirectional with CA suffix)
- High reliability with wafer fabrication and assembly lot traceability
- All parts surge tested
- Low profile surface mount package
- Optional upscreening is available with various screening and conformance inspection options based on MIL-PRF-19500. Refer to [Hirel Non-Hermetic Product Portfolio](#) brochure on our web site for more details on the screening options.
- Suppresses transients up to 30,000 W @ 10/1000  $\mu$ s (see [Figure 1](#))
- Moisture classification is Level 1 with no dry pack required per IPC/JEDEC J-STD-020B
- RoHS compliant versions are available
- $3\sigma$  lot norm screening performed on standby current ( $I_D$ )

### APPLICATIONS / BENEFITS

- Protection from switching transients and induced RFI
- Protection from ESD, and EFT per IEC 61000-4-2 and IEC 61000-4-4
- Secondary lightning protection per IEC 61000-4-5 with 42 ohms source impedance:
  - Class 1,2,3,4,5: MPLAD30KP14A to 400CA
  - Class 5: MPLAD30KP14A to 400CA (short distance)
  - Class 5: MPLAD30KP14A to 220CA (long distance)
- Secondary lightning protection per IEC 61000-4-5 with 12 ohms source impedance:
  - Class 1,2,3: MPLAD30KP14A to 400CA
  - Class 4: MPLAD30KP14A to 220CA
- Secondary lightning protection per IEC 61000-4-5 with 2 ohms source impedance:
  - Class 2: MPLAD30KP10A to 400CA
  - Class 3: MPLAD30KP14A to 220CA
  - Class 4: MPLAD30KP14A to 110CA
- Pin injection protection per RTCA/DO-160F for Waveform 4 (6.4/69  $\mu$ s @ 25°C)\*:
  - Level 4: MPLAD30KP14A to 400CA
  - Level 5: MPLAD30KP14A to 260CA
- Pin injection protection per RTCA/DO-160F for Waveform 5A (40/120  $\mu$ s @ 25°C)\*:
  - Level 4: MPLAD30KP14A to 64CA
  - Level 5: MPLAD30KP14A to 26CA

\*See [MicroNote 132](#) for further temperature derating selection.




### PLAD

(The cathode is the metal base under the body of this device.)

Also available:

### PLAD15KP

(15,000 watts)

 [MPLAD15KP7.0A thru MPLAD15KP200CA](#)

### MSC – Lawrence

6 Lake Street,  
Lawrence, MA 01841  
Tel: 1-800-446-1158 or  
(978) 620-2600  
Fax: (978) 689-0803

### MSC – Ireland

Gort Road Business Park,  
Ennis, Co. Clare, Ireland  
Tel: +353 (0) 65 6840044  
Fax: +353 (0) 65 6822298

### Website:

[www.microsemi.com](http://www.microsemi.com)

**MAXIMUM RATINGS @ 25 °C unless otherwise specified**


Parameters/Test Conditions	Symbol	Value	Unit	
Junction and Storage Temperature	T <sub>J</sub> and T <sub>STG</sub>	-55 to +150	°C/W	
Thermal Resistance Junction-to-Ambient <sup>(1)</sup>	R <sub>θJA</sub>	50	°C/W	
Thermal Resistance Junction-to-Case	R <sub>θJC</sub>	1.0	°C/W	
Peak Pulse Power @ 10/1000 μs <sup>(2)</sup>	P <sub>PP</sub>	30,000	W	
t <sub>clamping</sub> (0 volts to V <sub>(BR)</sub> min)	Unidirectional	<100	ps	
	Bidirectional	<5	ns	
Forward Clamping Voltage @ 500 Amps <sup>(3)</sup>	V <sub>FS</sub>	4.0	V	
Forward Surge Current <sup>(3)</sup>	I <sub>FSM</sub>	1500	A	
Solder Temperature @ 10 s	T <sub>SP</sub>	260	°C	
Steady-State Power dissipation <sup>(5)</sup>	T <sub>A</sub> = 25 °C T <sub>C</sub> = 100 °C	P <sub>D</sub>	2.5 <sup>(1)</sup>	W
			50 <sup>(4)</sup>	W

- Notes:**
- When mounted on FR4 PC board with recommended mounting pad (see [pad layout](#)).
  - Also see [figures 1 and 2](#). With impulse repetition rate (duty factor) of 0.05% or less.
  - At 8.3 ms half-sine wave (unidirectional devices only).
  - Case temperature controlled on heat sink as specified.
  - See [MicroNote 134](#) for derating P<sub>PP</sub> when also applying steady-state power.

**MECHANICAL and PACKAGING**

- CASE: Void-free transfer molded thermosetting epoxy body meeting UL94V-0
- TERMINALS: Tin-lead or RoHS compliant annealed matte-tin plating readily solderable per MIL-STD-750, method 2026
- MARKING: Body marked with part number
- POLARITY: For unidirectional devices, the cathode is on the metal backside (package bottom)
- Available in bulk or custom tape-and-reel packaging
- TAPE-AND-REEL: Standard per EIA-481-B (add "TR" suffix to part number). Consult factory for quantities.
- WEIGHT: Approximately 1.7 – 2.0 grams
- See [Package Dimensions](#) on last page.

**PART NOMENCLATURE**



**SYMBOLS & DEFINITIONS**

Symbol	Definition
$I_{(BR)}$	Breakdown Current: The current used for measuring breakdown voltage $V_{(BR)}$ .
$I_D$	Standby Current: The current at the rated standoff voltage $V_{WM}$ .
$I_{PP}$	Peak Impulse Current: The peak current during the impulse.
$V_{(BR)}$	Breakdown Voltage: The minimum voltage the device will exhibit at a specified current.
$V_C$	Clamping Voltage: Clamping voltage at $I_{PP}$ (peak pulse current) at the specified pulse conditions (typically shown as maximum value).
$V_{WM}$	Rated Working Standoff Voltage: The maximum peak voltage that can be applied over the operating temperature range.
$\alpha_{V(BR)}$	Temperature Coefficient of Breakdown Voltage: The change in breakdown voltage divided by change in temperature.


**ELECTRICAL CHARACTERISTICS @ 25 °C unless otherwise stated**

MICROSEMI PART NUMBER		REVERSE STANDOFF VOLTAGE $V_{WM}$ (Note 1)	BREAKDOWN VOLTAGE  $V_{(BR)}$ @ $I_{(BR)}$		MAXIMUM CLAMPING VOLTAGE $V_C$ @ $I_{PP}$	MAXIMUM STANDBY CURRENT $I_D$ @ $V_{WM}$	MAXIMUM PEAK PULSE CURRENT $I_{PP}$ (FIG. 3)	MAXIMUM TEMPERATURE COEFFICIENT $\alpha_{V(BR)}$
Unidirectional	Bidirectional	Volts	Volts	mA	Volts	$\mu A$	A	mV/ °C
MPLAD30KP14A	MPLAD30KP14CA	14	15.6 – 17.2	150	24.0	3000	1251*	10
MPLAD30KP15A	MPLAD30KP15CA	15	16.7 – 18.5	5	25.8	750	1164*	12
MPLAD30KP16A	MPLAD30KP16CA	16	17.8 – 19.7	5	27.2	450	1101*	12
MPLAD30KP17A	MPLAD30KP17CA	17	18.9 – 20.9	5	28.8	150	1041*	14
MPLAD30KP18A	MPLAD30KP18CA	18	20.0 – 22.1	5	30.8	60	975	16
MPLAD30KP20A	MPLAD30KP20CA	20	22.2 – 24.5	5	34.0	45	882	18
MPLAD30KP22A	MPLAD30KP22CA	22	24.4 – 26.9	5	36.4	10	822	20
<b>MPLAD30KP24A</b>	<b>MPLAD30KP24CA</b>	24	26.7 – 29.5	5	39.8	10	753	22
MPLAD30KP26A	MPLAD30KP26CA	26	28.9 – 31.9	5	43.0	10	696	24
MPLAD30KP28A	MPLAD30KP28CA	28	31.1 – 34.4	5	46.4	10	645	26
MPLAD30KP30A	<b>MPLAD30KP30CA</b>	30	33.3 – 36.8	5	48.8	10	618	30
MPLAD30KP33A	MPLAD30KP33CA	33	36.7 – 40.6	5	53.3	10	564	35
MPLAD30KP36A	<b>MPLAD30KP36CA</b>	36	40.0 – 44.2	5	58.1	10	516	38
MPLAD30KP40A	MPLAD30KP40CA	40	44.4 – 49.1	5	64.5	10	468	44
MPLAD30KP43A	MPLAD30KP43CA	43	47.8 – 52.8	5	69.4	10	432	50
MPLAD30KP45A	MPLAD30KP45CA	45	50.0 – 55.3	5	72.7	10	414	51
<b>MPLAD30KP48A</b>	MPLAD30KP48CA	48	53.3 – 58.9	5	77.4	10	390	54
MPLAD30KP51A	<b>MPLAD30KP51CA</b>	51	56.7 – 62.7	5	82.4	10	366	58
MPLAD30KP54A	MPLAD30KP54CA	54	60.0 – 66.3	5	87.1	10	342	64
MPLAD30KP58A	MPLAD30KP58CA	58	64.4 – 71.2	5	93.6	10	318	70
MPLAD30KP60A	MPLAD30KP60CA	60	66.7 – 73.7	5	96.8	10	312	72
MPLAD30KP64A	MPLAD30KP64CA	64	71.1 – 78.6	5	103.0	10	294	75
MPLAD30KP70A	MPLAD30KP70CA	70	77.8 – 86.0	5	113	10	264	84
MPLAD30KP75A	<b>MPLAD30KP75CA</b>	75	83.3 – 92.1	5	121	10	246	90
MPLAD30KP78A	MPLAD30KP78CA	78	86.7 – 95.8	5	126	10	240	95
MPLAD30KP85A	MPLAD30KP85CA	85	94.4 – 104.0	5	137	10	216	104
MPLAD30KP90A	MPLAD30KP90CA	90	100 – 111	5	146	10	204	109
MPLAD30KP100A	MPLAD30KP100CA	100	111 – 123	5	162	10	186	122
MPLAD30KP110A	MPLAD30KP110CA	110	122 – 135	5	177	10	168	132
MPLAD30KP120A	MPLAD30KP120CA	120	133 – 147	5	193	10	156	145
MPLAD30KP130A	MPLAD30KP130CA	130	144 – 159	5	209	10	142	157
MPLAD30KP150A	MPLAD30KP150CA	150	167 – 185	5	243	10	124	183
MPLAD30KP160A	MPLAD30KP160CA	160	178 – 197	5	259	10	116	195
<b>MPLAD30KP170A</b>	<b>MPLAD30KP170CA</b>	170	189 – 209	5	275	10	110	207
MPLAD30KP180A	MPLAD30KP180CA	180	200 – 221	5	291	10	104	219
MPLAD30KP200A	MPLAD30KP200CA	200	222 – 245	5	322	10	94	243
MPLAD30KP220A	MPLAD30KP220CA	220	245 – 271	5	356	10	84	269
MPLAD30KP260A	<b>MPLAD30KP260CA</b>	260	289 – 320	5	419	10	71	318
<b>MPLAD30KP280A</b>	MPLAD30KP280CA	280	311 – 345	5	451	10	66	344
MPLAD30KP300A	MPLAD30KP300CA	300	333 – 369	5	483	10	62	368
<b>MPLAD30KP350A</b>	MPLAD30KP350CA	350	389 – 431	5	564	10	53	430
MPLAD30KP400A	MPLAD30KP400CA	400	444 – 492	5	644	10	46	490


**NOTE 1:** Transient Voltage Suppressors are normally selected with reverse standoff voltage  $V_{WM}$ , which should be equal to or greater than peak operating voltage.

**NOTE 2:** Items listed in bold above are available ex-stock or with a short lead-time.

\* Surge Testing is performed to 1000Amps due to Equipment limitations


**GRAPHS**


**FIGURE 1**  
Peak Pulse Power vs. Pulse Time




**Figure 2**  
Pulse Waveform


**GRAPHS (continued)**



**FIGURE 3**  
Derating Curve

**PACKAGE DIMENSIONS**


Ref.	Dimensions			
	Inch		Millimeters	
	Min	Max	Min	Max
<b>A1</b>	0.485	0.495	12.32	12.57
<b>A2</b>	0.445	0.455	11.30	11.56
<b>B</b>	0.145	0.155	3.68	3.94
<b>C</b>	0.585	0.595	14.86	15.11
<b>D</b>	0.200	0.210	5.08	5.33
<b>F</b>	0.008	0.013	0.20	0.33
<b>G</b>	0.055	0.065	1.40	1.65
<b>H</b>	0.015	0.025	0.38	0.64
<b>J</b>	0.062 TYP.		1.57 TYP.	
<b>r1</b>	0.030 TYP.		0.76 TYP.	
<b>r2</b>	0.045 TYP.		1.14 TYP.	

**PAD LAYOUT**


Ref.	Dimensions			
	Inch		Millimeters	
	Min	Max	Min	Max
<b>A</b>	0.465	0.475	11.81	12.07
<b>B</b>	0.225	0.235	5.72	5.97
<b>C</b>	0.095	0.105	2.41	2.67
<b>D</b>	0.04	0.05	1.02	1.27