imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






Data Sheet MS15 30004



Mechanical Specifications (mm)

| 17.0 | ± max |
|------|----------------------------------|
| 8.0 | ± max |
| 1.0 | ± nom |
| 7.8 | ± nom |
| 38.0 | ± nom |
| 4.0 | ± max |
| 4.00 | ± nom |
| 6.00 | ± nom |
| | 8.0 1.0 7.8 38.0 4.0 |



Electrical Specifications

| Resistance: | 30.0 Ω | ± 25 % |
|---------------------------------------|--------|--------|
| Max Steady State Current upto 65°c: | 4.20 | А |
| Max Rec. Energy Rating: | 135 | J |
| Actual Failure Instantaneous Energy: | 270 | J |
| Maximum Capacitance @ 120 VAC: | 9,300 | μf |
| Maximum Capacitance @ 240 VAC: | 2,344 | μf |
| Maximum Capacitance @ 440 VAC: | 541 | μf |
| Maximum Capacitance @ 680 VAC: | 270 | μf |
| Resistance @ 100% Max Current: | 0.23 | Ω |
| Resistance @ 50% Max Current: | 0.87 | Ω |
| Body Temperature at 100% Max Current: | 150.00 | °C |
| Dissipation Constant: | 49.4 | mw/°c |
| Thermal Time Constant: | 114 | Sec. |
| Material Type (for Beta and Curve): | Н | |

| MS15 30004 | | |
|--|--------------------------|--|
| Date: 02/05/2009 | Drawn by: Erin Landis | |
| Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com | Approved By: Mehdi Samii | |
| | Revison: a | |