

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







# **SocketEthernet IP®**

Intelligent Serial-to-Ethernet Device Server




#### **Universal Socket Benefits**

- Interchangeable communications devices
- Intelligent Universal IP stack
- Quick-to-market
- Easy migration to future networks

The SocketEthernet IP® intelligent device server connects serial devices to an IP network via a 10/100BaseT Ethernet interface. It enables you to build IP networking into virtually any device allowing for remote monitoring, control and configuration. The space efficient communications device (1" x 2.5") integrates Multi-Tech's intelligent Universal IP® stack, and can make your existing and next generation device, machine or system, IP-ready while you focus on developing its core features.

#### **Features**

- Complete serial-to-Ethernet connectivity solution including network processor, media access controller and physical interface
- Serial interface supports DTE speeds to 230K bps
- Universal Socket connectivity
- Intelligent Universal IP stack for enhanced M2M functionality
- LED driver outputs for visual monitoring of speed, link, activity, collision and duplex mode
- 10/100BaseT auto-sensing Ethernet or configurable for 10MB, 100MB, half-duplex or full-duplex
- Models with medical/high voltage isolation (EN60601)
- AT command compatible
- Flash memory to update firmware with the latest enhancements
- Developer's kit available for testing, programming and evaluation
- Two year warranty





### **Highlights**

**Applications.** The SocketEthernet IP device server will IP-enable any serial device to provide remote monitoring, control and configuration of any system. It is ideal for:

- Appliances
- ATM terminals
- Credit card and check verification systems
- Data collection
- Gas pumps
- Industrial and medical remote monitoring systems
- Point-of-sale terminals
- Remote diagnostics
- Remote metering
- Security systems
- Television set-top boxes
- Ticketing machines
- Vending/gaming machines


Serial-to-Ethernet Technology. The SocketEthernet IP device server provides the powerful ability to IP-enable serial devices allowing more options for data acquisition, device management, and industrial control than would otherwise be available. The communications device integrates a processor, operating system, Universal IP stack and a network connection to provide a complete serial-to-Ethernet connectivity solution.

Universal Socket Connectivity. Multi-Tech's Universal Socket is a flexible, comm-port architecture that provides cellular, Ethernet, PSTN or Wi-Fi network access with interchangeable communications devices. This means you can utilize one system design and populate it with your connectivity device of choice accommodating multiple connectivity requirements. In addition, you are assured a seamless migration to future technologies.

Universal IP. Multi-Tech's Universal IP consists of a common set of TCP/IP networking protocols and machine-to-machine (M2M) applications implemented using a standard AT command interface. Universal IP allows developers to write their host application one time while having the freedom to select from a growing number of Universal Socket communication devices.

**SocketEthernet IP Pin-Out.** The SocketEthernet IP device server interfaces easily with existing products through a standard

serial communication channel. The serial DTE channel is capable of transfer speeds to 230.4K bps and can be interfaced directly to a UART or microcontroller. The SocketEthernet IP device server also provides LED driver outputs for visual monitoring of speed, link, activity, collision



Developer's Kit. The Developer's Kit allows you to plug in the communications device and use it for testing, programming and evaluation. The kit includes one development board with RS-232 DB-25 connector, universal power supply, RJ-45 jack and RS-232 cable.

## **Specifications**

#### Interfaces

10/100BaseT Ethernet, Asynchronous Serial

#### Power Requirements

5VDC or 3.3VDC

#### Power Usage

Typical: 137mA (.41w @ 3.3VDC) Maximum: 168mA (.50w @ 3.3VDC) Typical: 187mA (.94w @ 5VDC) Maximum: 194mA (.97w @ 5VDC)

#### Physical Description

2.541" L × 1.045" W × 0.680" H; 0.6 oz.  $(6.45 \text{ cm} \times 2.65 \text{ cm} \times 1.7 \text{ cm}; 0.017 \text{ kg.})$ 

#### Operating Environment

Temperature Range: -40° to +85° C

#### **Approvals**

EMC: FCC Part 15 Class B, Canada Class B, EN 55022 Class B, EN 55024

Safety: UL 60950, cUL 60950, EN 60950, CSA 950, AS/NZS 6950:2000

RoHS 2002/95/EC Compliant

## **Ordering Information**

**Product** MT100SEM-IP

MT100SEM-L-IP MT100SEM-L-HV-IP

Ordering Codes

-IP -L -HV Description Intelligent Device Server Intelligent Device Server

Intelligent Device Server

Region Global Global Global

Embedded Universal IP Stack 3.3V Power Input (Default is 5V) High Voltage Dielectric Isolation (EN60601)

Version control

Produced in the US of US and non-US components.

Features and specifications are subject to change without notice.

Trademarks / Registered Trademarks: SocketEthernet IP, Universal IP, Multi-Tech, and the Multi-Tech logo: Multi-Tech Systems, Inc. / All other products and technologies are the trademarks or registered trademarks of their respective holders.

World Headquarters Tel: (763) 785-3500

(800) 328-9717 www.multitech.com

and duplex mode.

**EMEA Headquarters** 

Multi-Tech Systems (EMEA) United Kingdom Tel: +(44) 118-959 7774

Multi-Tech Systems (EMEA) Tel: +(33) 1 49 19 22 06

.Rx

