imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SocketWireless[®] Wi-Fi[®]

Embedded Serial-to-Wi-Fi Device Server




Universal Socket Benefits

- Interchangeable communications devices
- Quick-to-market
- Global approvals
- Easy migration to future networks

The SocketWireless® Wi-Fi® device server connects serial devices to an IP network via 802.11b wireless networking. It enables you to build wireless networking into virtually any device allowing for remote monitoring, control and configuration. The space efficient communications device (1" x 2.5") integrates a complete TCP/IP protocol stack, and can make your existing and next generation device, machine or system, IP-ready while you focus on developing its core features.

Features

- Complete serial-to-Wi-Fi wireless connectivity solution including network processor, media access controller and air interface
- Supports ad-hoc and infrastructure mode
- Wi-Fi security using WEP
- Serial interface supports DTE speeds to 230K bps
- Space efficient universal socket connectivity
- High performance processor runs ARP, DHCP client, DNS, FTP client, ICMP (ping), IP, POP3, SMTP, TCP and UDP protocols
- Two LED driver outputs for visual monitoring of link and activity
- Configuration and management via AT commands
- Flash memory to update firmware with the latest enhancements
- Developer's kit available for testing, programming and evaluation
- Two-year warranty







Highlights

Applications. The SocketWireless Wi-Fi device server will wirelessly IP-enable any device to provide remote monitoring, control and configuration of any system. It is ideal for:

- Appliances
- ATM terminals
- Credit card and check verification systems
- Data collection
- Gas pumps
- Remote metering Security systems
- Television set-top boxes

• Point-of-sale terminals

• Remote diagnostics

- Industrial and medical remote monitoring systems
- Ticketing machines
- Vending/gaming machines

Serial-to-Wi-Fi Technology The SocketWireless Wi-Fi IP device server provides the powerful ability to IP-enable serial devices allowing more options for data acquisition, device management, and industrial control than would otherwise be available. The communications device integrates a processor, proprietary operating system, TCP/IP stack, and an 802.11b wireless network connection to provide a complete serial-to-Wi-Fi connectivity solution.

Quick-to-Market Solution. The complete, ready-to-integrate SocketWireless Wi-Fi device server is certified by the U.S. Federal Communications Commission (FCC). The FCC approval is portable across any solution for which the communications device is integrated, which means you can use the Multi-Tech license and bypass your own 802.11 regulatory product testing. This alone will save you valuable resources and dollars to allow you to focus on your product's core features, and accelerate your time-to-market.

Universal Socket Connectivity. Multi-Tech's universal socket is a flexible, comm-port architecture that provides cellular, Ethernet, PSTN or Wi-Fi network access with interchangeable communications devices. This means you can utilize one system design and populate it with your connectivity device of choice accommodating multiple connectivity requirements. In addition, you are assured a seamless migration to future technologies.

SocketWireless Wi-Fi Pin-Out. The SocketWireless Wi-Fi device server interfaces easily with existing products

through a standard serial communication channel. The serial DTE channel is capable of transfer speeds to 230.4K bps and can be interfaced directly to a UART or microcontroller. The SocketWireless Wi-Fi device server also provides two LED driver outputs for visual monitoring of link and activity.

(I/O) Tip 1 (I/O) Ring 2 Safety Void 3 (O) TX+ 4 (O) TX- 5 (I) RX+ 6	00×000		000000	64 SPKR (O) 63 GND (O) 62 MICV (I) 61 VCC (I) 60 -LED SPD (O) 59 -LED COL (O)
(I) RX- 7 Safety Void 8 9 10	° ×		000	58 -LED LINK (O) 57 -LED ACT (O) 56 -LED FDX (O) 55
(O) TXCLK 11 (O) RXCLK 12 13 14	00	Universal Socket	0	54 53 52 51 GPIO (I/O)
15 16 17 18 19 20 (1) 21		SocketWireless Wi-Fi	0000	50 GPIO (I/O) 49 GPIO (I/O) 48 GPIO (I/O) 47 46 45 44
(I) 21 (I) Mic+ 22 (I) Mic- 23 (I) -Reset 24 (I) USB_VBUS 25 (I) GND 26 (I/O) USB_DP 27 (I/O) USB_DN 28 (O) LED DCD 29 (O) LED DCD 32 (O) LED DTX 31 (O) LED TX 32	000000000000		000000000000	44 43 SPK+ (O) 42 SPK- (O) 41 GND (I) 40 -DTR (I) 39 -DCD (O) 38 -CTS (O) 37 -DSR (O) 36 -RI (O) 35 -TXD (I) 34 -RXD (O) 33 -RTS (I)

World Headquarters Tel: (763) 785-3500 (800) 328-9717

www.multitech.com

EMEA Headquarters Multi-Tech Systems (EMEA) United Kingdom Tel: +(44) 118-959 7774

Developer's Kit. The Developer's Kit allows you to plug in the communications device and use it for testing, programming and evaluation. The kit includes one development board with RS-232 DB-25 connector, universal power supply, antenna and RS-232 cable.

Specifications

Wireless Specifications

Network Interface: IEEE 802.11b Frequency Range: 2.400 to 2.484 GHz Data Rate: 1, 2, 5.5, 11Mbps Maximum Transmit Power: 16 dBm Receiver Sensitivity: -82 dBm Security: 64/128 bit WEP Mode: Ad Hoc, Infrastructure Antenna Connector: MMCX

Serial Interface

Data Format: Serial, asynchronous, 3.3V-level signals Data Rate: Software selectable (1200 bps – 230K bps)

Power Requirements

3.3VDC or 5VDC

Power Usage

Typical – 400mA @ 3.3VDC, 240mA @ 5VDC

Network Protocol Support

ARP, DHCP client, DNS, FTP client, ICMP (ping), IP, POP3 client, SMTP client, TCP, & UDP protocols

Physical Description

2.541" L × 1.045" W × 0.680" H; 0.6 oz. (6.45 cm × 2.65 cm × 1.7 cm; 0.017 kg.)

Operating Environment

Temperature Range: -30° to +70° C

Approvals

Safety: UL 60950, cUL 60950, EN 60950, AS/NZS 6950:2000 EMC: FCC Part 15 Subpart C, Canada, RSS-210, EN 300 328, EN 301 489-17

Ordering Information

Product MT800SWM MT800SWM-L

Description 802.11b Device Server, 5V 802.11b Device Server, 3.3V

Region Regional Regional

Made in Mounds View, MN, U.S.A.

Features and specifications are subject to change without notice.

Trademarks / Registered Trademarks: SocketWireless, Multi-Tech, and the Multi-Tech logo: Multi-Tech Systems, Inc. / Wi-Fi is a registered trademark of the Wi-Fi Alliance. / All other products and technologies are the trademarks or registered trademarks of their respective holders.

Multi-Tech Systems (EMEA) France Tel: +(33) 1 49 19 22 06



9/07 86002080