



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SocketSLIC®

Analog Telephony Interface Module




The SocketSLIC® interface module is a complete, ready-to-integrate isolated and programmable analog-to-PCM interface. It allows the user to choose the appropriate telephony interface when the system is configured either in manufacturing or in the field. This flexibility adds convenience, low cost and quick time to market to designing modern communication systems or updating existing telephony systems. The SocketSLIC interface module takes care of the many standard analog interfaces allowing the designer to focus on the digital design.

Features

- Analog port supports standard telephony interfaces
- Digital port supports standard TDM interfaces
- Control port supports standard serial interfaces
- Supports FXO, FXS, DPO, DPT, E&M, PLR, ETO, TO
- Loop-Start, Ground-Start, Direct-Inward-Dialing (DID)
- E&M Type I, II, III, IV and V signaling
- Two-wire and four-wire transmissions
- Supports Caller ID service and other CLASS services
- Provides loop-disconnect signals
- On-board ring generator and power supply
- Adjustable telecom battery voltage
- Adjustable transmit and receive levels
- Adjustable ringing voltage and ringing frequency
- FCC Part 68, CS-03, TBR21 approved
- No DIP switches or jumpers
- Single +5VDC supply voltage
- Low power consumption
- Small footprint

Benefits

- Field Programmable
- Operating System Independent
- Bellcore Compliant
- Isolated Analog Telephony Interface




Highlights

Applications. The flexible analog line card interface is ideal for:

- Automatic call distributors
- Digital loop carriers
- Fax boards
- Fax servers
- Fiber-in-the-loop
- Hybrid-fiber/Coax
- Key systems
- Modems
- Multiplexers
- PBX, PC-PBX, IP-PBX
- Remote terminals
- Voice processing boards
- VOIP gateways
- Wireless local loop

Module Interface Ports and Pins. The SocketSLIC interface module uses channel associated signaling (A and B bits) to control the analog interface. (It can be programmed to support unique interfaces per specific customer installation requirements.)



Reduces Development Time. The SocketSLIC interface module actually provides faster time-to-market because it relieves the burden and expense of designing the analog interface. This complete, ready-to-integrate analog module allows you to enhance your product while you focus on developing its core features.

Who's Multi-Tech? Multi-Tech Systems is an ISO 9001:2000 certified global manufacturer of award-winning telephony, Internet, remote access and device networking products that connect voice and data over IP networks. Within a 34 year history inventing products known for their reliability and performance, Multi-Tech still employs the same mission from which the company was founded: to provide quality solutions that solve real business problems. To reinforce this philosophy, Multi-Tech prides itself on developing and fostering mutually beneficial long-term relationships with its worldwide network of technology partners, sales channels and customers.

Specifications

Ports Per Module

- Analog Port: 1 (Telephony interface)
- Digital Port: 1 (TDM interface)
- Control Port: 1 (Serial interface)

Standard Telephony Interfaces

- Foreign Exchange Subscriber (FXS): Loop-Start or Ground-Start
- Foreign Exchange Office (FXO): Loop-Start or Ground-Start
- Dial Pulse Originating (DPO): Direct-Inward-Dialing
- Dial Pulse Terminating (DPT): Direct-Inward-Dialing
- E&M Signaling (E&M): 2-wire or 4-wire, Type I-V
- Pulse Link Repeater (PLR): 2-wire or 4-wire, Type I-V
- Transmission Only (TO): 2-wire
- Equalized Transmission Only (ETO): 4-wire

Standard TDM Interfaces

- AT&T: Concentration Highway Interface
- Multi-Vendor Integration Protocol (MVIP)
- Mitel: ST-Bus
- Siemens: PCM Highway

Standard Serial Interfaces

- SPI Interface: 3-wire synchronous
- UART Interface: 2-wire asynchronous

Power Requirements

- Voltage: +5VDC
- Tolerance: +/-5%
- Current: 0.1 A maximum
- Power: 0.5 W maximum

Dimensions

- 3.750" L x 1.065" W x 0.540" H
- (9.525cm x 2.705cm x 1.372cm)

Environmental

- Operating Temp: +32° to +104° F (0° to +40° C)
- Storage Temp: -40° to +185° F (+4° to +85° C)
- Humidity: 5% to 95% non-condensing

Approvals

- CE Mark
- EMC: FCC Part 15 Class A, EN 55022, EN 55024
- Safety: UL 60950, EN 60950
- Telecom: FCC Part 68, CS-03, TBR21

Ordering Information

Product	Description	Region
MTIFM	Telephony Interface Module	US/Can/Euro

Made in Mounds View, MN, U.S.A.

Features and specifications are subject to change without notice.

Trademarks / Registered Trademarks: SocketSLIC, Multi-Tech, and the Multi-Tech logo: Multi-Tech Systems, Inc. / All other products and technologies are the trademarks or registered trademarks of their respective holders.

World Headquarters
Tel: (763) 785-3500
(800) 328-9717
www.multitech.com

EMEA Headquarters
Multi-Tech Systems (EMEA)
United Kingdom
Tel: +(44) 118-959 7774

Multi-Tech Systems (EMEA)
France
Tel: +(33) 1 64 61 09 81