

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China










# Scotchlok<sup>™</sup> Terminals

# MVU18BC, MVU14BC, MVU10BC Butt Connector, Vinyl Insulated, Butted Seam



## **Data Sheet**

Product Number	Wire Range (AWG)	L	Thickness	Barrel Length	Barrel I.D.	Maximum Insulation Diameter
MVU18BC	22-18	1.00	0.030	0.25	0.070	0.145
MVU14BC	16-14	1.00	0.030	0.25	0.090	0.170
MVU10BC	12-10	1.02	0.040	0.25	0.135	0.250



UNDERWRITERS LABORATORIES STANDARD NO. UL 486C 3M FILE NO. E23438



CANADIAN STANDARDS ASSOCIATION STANDARD NO. 22.2 NO. 0, 65 3M FILE NO. LR22190

### **Installation Information**

### **WARNING**

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 5/16 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style) or TR-490 (ratchet style) hand tools.

Barrel Crimp (Required)

### **Specifications**

Wire Size: Barrel Seam:

Insulator Max. Volt Rating:

Maximum Operating Temp.: Maximum Current: Insulator Material: Terminal Material: Terminal Plating:

See Table Above **Butted** 

600 V Building Wire:

1000 V Signs or Fixtures (Luminaires) 221°F (105°C)

Same as Wire Vinyl ETP Copper

Tin

3M is a trademark of 3M Company.

(Ų

is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, Indirect, special, Incidental or consequential regardless of the legal theory asserted.

**3M** 

Electrical Markets Division 6801 River Place Blvd. Austin, TX 78726-9000 www.3M.com/electrical

Litho in USA © 3M 2004 78-8125-9668-8-B