



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



N-CHANNEL J-FET

Equivalent To MIL-PRF-19500/385

DEVICES

2N4856 2N4858 2N4860
2N4857 2N4859 2N4861

LEVELS

MQ = JAN Equivalent
MX = JANTX Equivalent
MV = JANTXV Equivalent

ABSOLUTE MAXIMUM RATINGS ($T_C = +25^\circ\text{C}$ unless otherwise noted)


Parameters / Test Conditions	Symbol	2N4856	2N4859	Unit
		2N4857 2N4858	2N4860 2N4861	
Gate-Source Voltage	V_{GS}	-40	-30	V
Drain-Source Voltage	V_{DS}	40	30	V
Drain-Gate Voltage	V_{DG}	40	30	V
Gate Current	I_G	50		mA
Power Dissipation	P_T	$T_A = +25^\circ\text{C}^{(1)}$		W
		$T_C = +25^\circ\text{C}^{(2)}$		W
Operating Junction & Storage Temperature Range	T_J, T_{stg}	-65 to + 200		$^\circ\text{C}$

(1) Derate linearly 2.06 mW/ $^\circ\text{C}$ for $T_A > +25^\circ\text{C}$.

(2) Derate linearly 10.3 mW/ $^\circ\text{C}$ for $T_C > +25^\circ\text{C}$.

ELECTRICAL CHARACTERISTICS ($T_A = +25^\circ\text{C}$, unless otherwise noted)

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Gate-Source Breakdown Voltage $V_{DS} = 0, I_G = -1.0\mu\text{A dc}$	$V_{(BR)GS}$	2N4856, 2N4857, 2N4858	-40	Vdc
		2N4859, 2N4860, 2N4861	-30	
Gate-Source "Off" State Voltage $V_{DS} = 15\text{V dc}$ $I_D = 0.5\eta\text{A dc}$	$V_{GS(off)}$	2N4856, 2N4859	-4.0	Vdc
		2N4857, 2N4860	-2.0	
		2N4858, 2N4861	-0.8	
Gate Reverse Current $V_{DS} = 0, V_{GS} = -20\text{V dc}$ $V_{DS} = 0, V_{GS} = -15\text{V dc}$	I_{GSS}	2N4856, 2N4857, 2N4858	-0.25	ηA
		2N4859, 2N4860, 2N4861	-0.25	
Drain Current Cutoff $V_{GS} = -10\text{V dc}, V_{DS} = 15\text{V dc}$	$I_{D(off)}$		0.25	ηA
Drain Current Zero Gate Voltage $V_{GS} = 0, V_{DS} = 15\text{V dc}$	I_{DSS}	2N4856, 2N4859	50	mA
		2N4857, 2N4860	20	
		2N4858, 2N4861	8.0	
Drain-Source "On" State Voltage $V_{GS} = 0, I_D = 20\text{mA dc}$ $V_{GS} = 0, I_D = 10\text{mA dc}$ $V_{GS} = 0, I_D = 5.0\text{mA dc}$	$V_{DS(on)}$	2N4856, 2N4859	0.75	Vdc
		2N4857, 2N4860	0.50	
		2N4858, 2N4861	0.50	
Static Drain - Source "On" State Resistance $V_{GS} = 0, I_D = 1.0\text{mA dc}$	$r_{ds(on)}$	2N4856, 2N4859	25	Ω
		2N4857, 2N4860	40	
		2N4858, 2N4861	60	



TO-18
(TO-206AA)



6 Lake Street, Lawrence, MA 01841
 1-800-446-1158 / (978) 620-2600 / Fax: (978) 689-0803
 Website: <http://www.microsemi.com>

TECHNICAL DATA SHEET

N-CHANNEL J-FET Equivalent To MIL-PRF-19500/385

DYNAMIC CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Small-Signal, Common Short-Circuit Reverse Transfer Capacitance $V_{GS} = -10V$ dc, $V_{DS} = 0$, $f = 1.0MHz$ $C_1 = 0.1\mu F$, $L_1 = L_2 \geq 500\mu H$	C_{rss}		8.0	pF
Small-Signal, Common-Source Short-Circuit Input Capacitance $V_{GS} = -10V$ dc, $V_{DS} = 0$, $f = 1.0MHz$ $C_1 = 0.1\mu F$, $C_2 = 20.1\mu F$ $L_1 = L_2 \geq 500\mu H$	C_{iss}		18	pF

SWITCHING CHARACTERISTICS

Parameters / Test Conditions	Symbol	Min.	Max.	Unit
Turn-On Delay Time 2N4856, 2N4859 2N4857, 2N4860 2N4858, 2N4861	See Figure 3 of MIL-PRF-19500/385		6	ηs
Rise Time 2N4856, 2N4859 2N4857, 2N4860 2N4858, 2N4861			3 4 10	
Turn-Off Delay Time 2N4856, 2N4859 2N4857, 2N4860 2N4858, 2N4861			25 50 100	