



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Product Information

# MX6028GL Series

Compliant with IEC61850-3 and IEEE1613  
**28G-Port Rackmount Layer 3 Full Gigabit  
Managed Ethernet Switches**



## Features

- ❖ Supports RIP, OSPF, layer 3 routing protocols
- ❖ 24 Gigabit Ethernet ports
- ❖ Up to 28 optical fiber connections (SFP slots)
- ❖ Fanless, -40 to +85°C operating temperature range
- ❖ Universal 110/220VADC power supply range



Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

[www.henrich-inc.com](http://www.henrich-inc.com)

## Introduction

Process automation and transportation automation applications combine data, voice, and video, and consequently require high performance and high reliability. The MX6028GL series full Gigabit backbone switches are equipped with 24 x Gigabit Copper Port and 4 x Gigabit SFP Slots. They provide Layer 3 routing functionality to facilitate the deployment of applications across networks and make them ideal for large scale industrial networks. The MX6028GL's full Gigabit capability increases bandwidth to provide high performance and quickly transfer large amounts of video, voice, and data across a network. The switches support the RingOn and RSTP redundancy protocols, and are fanless and come with an isolated redundant power supply to increase system reliability and the availability of your network backbone.

## Specifications

Technology	
Standard :	IEEE802.3, 802.3u, 802.3ab, 802.3z, 802.3x, 802.1D, 802.1w, 802.1Q, 802.1p
Flow Control :	IEEE802.3x Flow Control, Back Pressure Flow Control
Protocols :	IGMP Snooping, GMRP, SNMPv1/v2c/v3, DHCP Client, HTTP, HTTPS, Telnet, NTP Client
Software functions :	<p><b>L3 Functions</b></p> <ul style="list-style-type: none"> <li>• Static IP routing</li> <li>• OSPFv1/v2</li> <li>• RIPv1/v2</li> <li>• VRRP</li> <li>• IGMP v2/v3 Multicast Listener Protocol</li> <li>• Firewall , NAT and port mapping</li> <li>• File sharing based on the SAMBA service</li> <li>• FTP service based on STUPID-FTP</li> <li>• SSH secure access service based on OPENSCH</li> <li>• Add access, control WEB</li> </ul> <p><b>L2 Functions</b></p> <ul style="list-style-type: none"> <li>• IEEE 802.1Q Static VLAN and VLAN Label</li> <li>• Link Layer Management Protocol (LLDP)</li> <li>• IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)</li> <li>• IGMP SNOOPING</li> <li>• RingOn™ Redundant Technology, recovery time &lt;15ms</li> <li>• RingOpen Redundancy</li> </ul> <p><b>Management Tools</b></p> <ul style="list-style-type: none"> <li>• Web Interface (HTTP and HTTPS)</li> <li>• Console port and Command Line Interface(CLI) controlled by SSHv2</li> <li>• SNMPv1/v2c/v3</li> <li>• Flexible configuration and log file management</li> <li>• Managing local file through HTTP, FTP, TFTP and SCP</li> <li>• Syslog(System log file and remote syslog server)</li> <li>• SNTP(NTP Client)</li> <li>• Software Online Upgrading</li> </ul>
Switch Properties	
L3 Host table :	4K
MAC Table Size :	16K
Priority Queues :	8
Max. Number VLANs :	256
VLAN ID Range :	VID 1 to 4094
IGMP Groups :	1000
Interface	
RJ45 Port :	10/100/1000M Auto-Negotiation, Full/Half Duplex, Auto-MDI/MDIX
Fiber Port :	100BaseFX (SC/ST connector) and 1000BaseSFP Slot
LED Indicators :	Power, Port Status, 10/100/1000M
Console port :	RJ45 Port
Output Warning :	Relay, Standard 2 Pin
Power Requirements	
Input Voltage :	48VDC @ 50W MAX 120~370VDC @ 50W MAX 85~265VAC @ 50VA MAX
Input Connection :	Grid panel terminal blocks Standard 4 pin input connection (optional)
Physical Characteristics	
Case :	Slim Metal Case, IP40 Design
Dimensions :	443×44×310mm
Installation :	Rack mounting
Optical Fiber	
Mode	Single Mode
Transmission Distance	20km
Centre Wavelength	1310nm
Cable Size	9/125um
TX Power(dBm)	-8~-2dBm
RX Power(dBm)	< -24dBm
Transmission Rate	1000Mbps
Environment Limits	
Operating Temp. :	Wide Temp. Models: -40 to 85°C
Storage Temp. :	-40 to 85°C
Ambient Relative Humidity :	5 to 95%(Non-condensing)

Standards and Certifications	
EMI :	FCC Part15, CISPR(EN55022) Class A
EMS :	EN61000-4-2(ESD) Level 4, EN61000-4-3(RS) Level 4, EN61000-4-4(EFT) Level 4, EN61000-4-5(Surge) Level 4, EN61000-4-6(CS) Level 4, EN61000-6-2
Shock :	IEC 60068-2-27
Freefall :	IEC 60068-2-32
Vibration :	IEC 60068-2-6

Warranty	
Warranty Period :	3 years

## Ordering Information

### MX6028GL Series

MX6028GL-4SFP-2VLW	Layer 3 Rackmount Managed, 24 x Gigabit Copper Port, 4 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 48VDC
MX6028GL-4SFP-VHW	Layer 3 Rackmount Managed, 24 x Gigabit Copper Port, 4 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 120~370VDC or 85~264VAC
MX6028GL-28SFP-2VLW	Layer 3 Rackmount Managed, 28 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 48VDC
MX6028GL-28SFP-VHW	Layer 3 Rackmount Managed, 28 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 120~370VDC or 85~264VAC