

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








SANYO Cadnica






Cell Type N-1900SCR **Specifications**


Nominal Capacity			1900mAh
Nominal Voltage			1.2V
Charging Current		Standard	190mA
		Fast	2900mA
Charging Time		Standard	14 to 16Hrs.
		Fast	about 1Hr.
Ambient Temperature	Charge	Standard	0°C to +45°C [+32°F to 113°F]
		Fast	5°C to +40°C [+41°F to 104°F]
	Discharge		-20°C to +60°C [-4°F to 140°F]
	Storage		-30°C to +50°C [-22°F to 122°F]
Internal Impedance (Av.) (at 50% discharge)			4.0mΩ (at 1000Hz)
Weight			54g/1.98oz
Dimensions(D)×(H) (with tube)			$ \begin{array}{cccccccccccccccccccccccccccccccccccc$

Typical Characteristics


Charge Characteristics (5 cells pack)




Cell Capacity (at various discharge rate)




Discharge (at low rate)




Discharge (at high rate)



Discharge (at high rate)



Temperature (Charge & Discharge)



CD010830