



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HP J4859C Compatible 1000Base-LX LC SFP Transceiver, DDM, Singlemode, 1310 nm, 10 km

MODEL NUMBER: N286-01GLX-SLX



Adds a duplex LC female connector to your HP 10/100/1000 network equipment.

Description

The N286-01GLX-SLX HP J4859C Compatible 1000Base-LX LC SFP Transceiver with a duplex LC female connector functions just like the HP J4859C transceiver module and is designed to operate with HP networking equipment. It also meets or exceeds the J4859C's original specifications and complies with MSA (Multi-Source Agreement) standards.

This 1000Base-LX transceiver is fully hot-pluggable, so you can install it without shutting down the network or rebooting your device. It supports data transfer rates up to 1 Gbps with 1310 nm wavelength signaling. It transmits across six miles (10 kilometers) of 9/125 SMF cabling.

The N286-01GLX-SLX also supports DDM, so you can monitor optical output power, optical input power, temperature, laser bias current and transceiver supply voltage. It is electrical interface-compliant with SFF-8431 specification.

Features

1000Base-LX Transceiver with Duplex LC Connector

- Hot-pluggable for installation without rebooting or shutting down
- Data transfer rates up to 1 Gbps
- Transmits up to 6 miles (10 km) with 9/125 SMF cabling
- Supports DDM
- Electrical interface-compliant with SFF-8431 specification
- 1310 nm wavelength signaling

Designed for Use with HP Networking Equipment

Highlights

- Supports data transfer rates up to 1 Gbps
- Transmits up to 6 mi. (10 km) with 9/125 SMF cabling
- Supports digital diagnostic monitoring (DDM)
- Complies with MSA standards
- 100% compatible with HP networking hardware

System Requirements

For a list of compatible switches, see the Switch Compatibility document in the Resources tab or the Technical Support page.

Package Includes

- N286-01GLX-SLX HP J4859C Compatible 1000Base-LX LC SFP Transceiver
- Owner's manual



- Functionally equivalent to HP J4859C
- Meets or exceeds J4859C specs
- Complies with MSA standards

Specifications

| OVERVIEW | |
|-------------------------------------|----------------------------------------------|
| UPC Code | 037332197436 |
| Accessories Type | Transceiver |
| Technology | SFP+/QSFP+/QSFP28 |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 1.10 x 3.60 x 4.60 |
| Shipping Dimensions (hwd / cm) | 2.79 x 9.14 x 11.68 |
| Shipping Weight (lbs.) | 0.10 |
| Shipping Weight (kg) | 0.05 |
| Unit Dimensions (hwd / in.) | 0.33 x 0.52 x 2.24 |
| Unit Dimensions (hwd / cm) | 0.84 x 1.32 x 5.69 |
| Unit Weight (lbs.) | 0.05 |
| Unit Weight (kg) | 0.02 |
| ENVIRONMENTAL | |
| Storage Temperature Range | -40 to 185 F (-40 to 85 C)0.33 x 0.52 x 2.24 |
| Relative Humidity | 10 to 85% RH, Non-Condensing |
| Operating Temperature | 32 to 158 F (0 to 70 C) |
| COMMUNICATIONS | |
| Signal Range (m) | 500 |
| CONNECTIONS | |
| Side A - Connector 1 | SFP+ (MALE) |
| Side B - Connector 1 | LC DUPLEX (FEMALE) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>