



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





NCP1072DIPGEVB:6 W SMPS Evaluation Board

Evaluation Board Description

The NCP1072 / NCP1075 products integrate a fixed frequency current mode controller with a 700 V MOSFET. Available in a PDIP-7 or SOT-223 package, the NCP1072/5 offer a high level of integration, including soft-start, frequency-jittering, short-circuit protection, skip-cycle, a maximum peak current set point, ramp compensation, and a Dynamic Self-Supply (eliminating the need for an auxiliary winding).



Design Support

- » [Technical Documentation](#)
- » [Design Resources](#)
- » [Technical Support](#)
- » [Sales Support](#)

Unlike other monolithic solutions, the NCP1072/5 is quiet by nature: during nominal load operation, the part switches at one of the available frequencies (65, 100 or 130 kHz). When the output power demand diminishes, the IC automatically enters frequency foldback mode and provides excellent efficiency at light loads. When the power demand reduces further, it enters into a skip mode to reduce the standby consumption down to a no load condition.

Protection features include: a timer to detect an overload or a short-circuit event, Overvoltage Protection with auto-recovery and AC input line voltage detection.

For improved standby performance, the connection of an auxiliary winding stops the DSS operation and helps to reduce input power consumption below 50 mW at high line.

Evaluation Board Information

| Evaluation Board | Status | Pb-free | Short Description | Parts Used | Action |
|--------------------------------|--------|---------|---------------------------|------------------------------|--------|
| NCP1072DIPGEVB | Active | | 6 W SMPS Evaluation Board | NCP1072P100G | |

Technical Documents

| Type | Document Title | Document ID/ Size | Rev |
|----------------------------|---|---|-----|
| Eval Board: BOM | NCP1072DIPGEVB Bill of Materials ROHS Compliant | NCP1072DIPGEVB_BOM_ROHS.PDF - 115.0 KB | 0 |
| Eval Board: Gerber | NCP1072DIPGEVB Gerber Layout Files (Zip Format) | NCP1072DIPGEVB_GERBER.ZIP - 35.0 KB | 0 |
| Eval Board: Schematic | NCP1072DIPGEVB Schematic | NCP1072DIPGEVB_SCHEMATIC.PDF - 162.0 KB | 0 |
| Eval Board: Test Procedure | NCP1072DIPGEVB Test Procedure | NCP1072DIPGEVB_TEST_PROCEDURE.PDF - 86.0 KB | 0 |

