



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NCP81074A, NCP81074B

Single Channel 10A High Speed Low-Side MOSFET Driver

The NCP81074 is a single channel, low-side MOSFET driver. It is capable of providing large peak currents into capacitive loads. This driver can deliver a 7 A peak current at the Miller plateau region to help reduce the Miller effect during MOSFETs switching transitions. It exhibits a split output configuration allowing the user to control the turn on and turn off slew rates. This part is available in SOIC-8 and DFN8 2x2 mm packages.

Features

- High Current Drive Capability ± 10 A
- TTL/CMOS Compatible Inputs Independent of Supply Voltage
- High Reverse Current Capability (10 A) Peak
- 4 ns Typical Rise and 4 ns Typical Fall Times with 1.8 nF Load
- Fast Propagation Delay Times of 15 ns with Input Falling and 15 ns with Input Rising
- Input Voltage Range from 4.5 V to 20 V
- Split Output Configuration
- Dual Input Design Offering Drive Flexibility
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

Applications


- Server Power
- Telecommunication, Datacenter Power
- Synchronous Rectifier
- Switch Mode Power Supply
- DC/DC Converter
- Power Factor Correction
- Motor Drive
- Renewable Energy, Solar Inverter




ON Semiconductor®

www.onsemi.com

MARKING DIAGRAMS




DFN8
MN SUFFIX
CASE 506AA




XX = Specific Device Code
M = Date Code
▪ = Pb-Free Device

(Note: Microdot may be in either location)



SOIC-8
CASE 751



XXXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb-Free Package

ORDERING INFORMATION

See detailed ordering, marking and shipping information on page 2 of this data sheet.

NCP81074A, NCP81074B

ORDERING INFORMATION

| Device | Temperature Range (°C) | Marking | Input Type | Package Type | Shipping [†] |
|----------------|------------------------|-----------|-------------------------|--------------------|-----------------------|
| NCP81074AMNTBG | –40 to +140 | CL | Fixed Digital Threshold | DFN8 2x2 (Pb-Free) | 3000 / Tape & Reel |
| NCP81074BMNTBG | –40 to +140 | CM | VDD Based Threshold | DFN8 2x2 (Pb-Free) | 3000 / Tape & Reel |
| NCP81074ADR2G | –40 to +140 | NCP81074A | Fixed Digital Threshold | SOIC–8 (Pb-Free) | 2500 / Tape & Reel |
| NCP81074BDR2G | –40 to +140 | NCP81074B | VDD Based Threshold | SOIC–8 (Pb-Free) | 2500 / Tape & Reel |

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

BLOCK DIAGRAM




Figure 1. NCP81074 Block Diagram

NCP81074A, NCP81074B

PIN DESCRIPTION

| Pin No. | Symbol | Description |
|---------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | IN+ | Non-Inverting Input which has logic compatible threshold and hysteresis. If not used, this pin should be connected to either VDD or GND. It should not be left unconnected. |
| 2 | GND | Common ground. This ground should be connected very closely to the source of the power MOSFET. |
| 3 | GND | Common ground. This ground should be connected very closely to the source of the power MOSFET. |
| 4 | OUTL | Sink pin. Connect to Gate of MOSFET. |
| 5 | OUTH | Source Pin. Connect to Gate of MOSFET. |
| 6 | VDD | Power Supply Input Pin. |
| 7 | VDD | Power supply Input Pin. |
| 8 | IN– | Inverting Input which has logic compatible threshold and hysteresis. If not used, this pin should be connected to either VDD or GND. It should not be left unconnected |




Figure 2. TYPICAL APPLICATION CIRCUIT

ABSOLUTE MAXIMUM RATINGS

| Parameter | | Value | | Unit |
|----------------------------------|--------------------------|-------|-----------|------|
| | | Min | Max | |
| Supply Voltage | VDD | −0.3 | 24 | V |
| Output Current (DC) | Iout_dc | 0.6 | | A |
| Reverse Current (Pulse<1 μs) | | | 10 | A |
| Output Current (Pulse<0.5 μs) | Iout_pulse | 10 | | A |
| Input Voltage | IN+, IN− | −6 | 24 | V |
| Output Voltages | OUTH, OUTL | −0.3 | VDD + 0.3 | V |
| Output Voltages (Pulse<0.5 μs) | OUTH, OUTL | −3.0 | VDD + 3.0 | V |
| Junction Operation Temperature | TJ | −40 | 150 | °C |
| Storage Temperature | Tstg | −65 | 160 | |
| Electrostatic Discharge | Human body model, HBM | 4000 | | V |
| | Charge device model, CDM | 1000 | | |
| OUT Latch-up Protection | | 500 | | mA |
| Moisture Sensitivity Level (MSL) | | MSL1 | | |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

NCP81074A, NCP81074B

RECOMMENDED OPERATING CONDITIONS

| Parameter | Rating | Unit |
|----------------------------|-------------|------|
| VDD supply Voltage | 4.5 to 20 | V |
| IN+, IN– input voltages | –5 to 20 | V |
| Junction Temperature Range | –40 to +140 | °C |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

Table 1. THERMAL INFORMATION

| Package | Theta JA (°C/W) | Theta JC (°C/W) |
|-----------|-----------------|-----------------|
| DFN–8 2x2 | 80.3 | 11.9 |
| SOIC–8 | 115 | 50 |

Table 2. ELECTRICAL CHARACTERISTICS (Note 1) (Typical values: VDD = 12V, 1uF from VDD to GND, TA = TJ = –40°C to 140°C, typical at TAMB = 25°C, unless otherwise specified)

| Parameter | SYMBOL | Test Conditions | MIN | TYP | MAX | Unit |
|-----------|--------|-----------------|-----|-----|-----|------|
|-----------|--------|-----------------|-----|-----|-----|------|

SUPPLY VOLTAGE

| | | | | | | |
|----------------------------------------------------|------|-------------|-----|-----|-----|----|
| VDD Under Voltage Lockout (rising) | VCCR | VDD rising | 3.7 | 3.9 | 4.1 | V |
| VDD Under Voltage Lockout (Falling) | VCCF | VDD falling | 3.4 | 3.6 | 3.8 | V |
| VDD Under Voltage Lockout (hysteresis) | VCHH | | | 300 | | mV |
| Operating Current (no switching) | IDD | | | 1.2 | 2 | mA |
| VDD Under Voltage Lockout to Output Delay (Note 1) | | VDD rising | | 10 | | μs |

INPUTS

| | | | | | | |
|--------------------------|-------------------------|---------------------------------------------------|----------|----------|----------|----|
| NCP81074A High Threshold | VthH | Input rising from logic low | 1.9 | 2.1 | 2.3 | V |
| NCP81074A Low Threshold | VthL | Input falling from logic high | 1.1 | 1.3 | 1.5 | V |
| VIN_HYS | Input Signal Hysteresis | | | 0.8 | | V |
| NCP81074B High Threshold | VthH | Input rising from logic low (VDD = 8 V to 12 V) | VDD –3.5 | VDD –3.1 | VDD –2.7 | V |
| NCP81074B Low Threshold | VthL | Input falling from logic high (VDD = 8 V to 12 V) | GND +2.6 | GND +2.9 | GND +3.2 | V |
| IN– Pull–up Resistor | Rin– | | | 200 | | kΩ |
| IN+ Pull–Down Resistor | Rin+ | | | 200 | | kΩ |

OUTPUTS

| | | | | | | |
|----------------------------------------------|---------|-----------------------------|--|-----|-----|---|
| Output Resistance High | ROH | IOUT = –10 mA | | 0.4 | 0.8 | Ω |
| Output Resistance Low | ROL | IOUT = +10 mA | | 0.4 | 0.8 | Ω |
| Peak Source Current ⁽²⁾ | ISource | OUT = GND 200 ns Pulse | | 10 | | A |
| Miller Plateau Source Current ⁽²⁾ | ISource | OUT = 5.0 V 200 ns Pulse | | 7 | | A |
| Peak Sink Current ⁽²⁾ | ISink | OUT = VDD 200 ns Pulse | | 10 | | A |
| Miller Plateau Sink Current ⁽²⁾ | ISink | OUT = 5.0 V 200 ns Pulse | | 7 | | A |

NCP81074A, NCP81074B

Table 2. ELECTRICAL CHARACTERISTICS (Note 1) (Typical values: $V_{DD} = 12V$, $1\mu F$ from V_{DD} to GND , $T_A = T_J = -40^\circ C$ to $140^\circ C$, typical at $T_{AMB} = 25^\circ C$, unless otherwise specified)

| Parameter | SYMBOL | Test Conditions | MIN | TYP | MAX | Unit |
|---------------------------------------------------------------------|----------|----------------------------|-----|-----|-----|------|
| SWITCHING CHARACTERISTICS | | | | | | |
| Propagation Delay Time Low to High, IN Rising (IN to OUT) (Note 2) | t_{d1} | $C_{Load} = 1.8\text{ nF}$ | | 15 | 27 | ns |
| Propagation Delay Time High to Low, IN Falling (IN to OUT) (Note 2) | t_{d2} | $C_{Load} = 1.8\text{ nF}$ | | 15 | 27 | ns |
| Rise Time (Note 2) | t_r | $C_{Load} = 1.8\text{ nF}$ | | 4 | 7 | ns |
| Fall Time (Note 2) | t_f | $C_{Load} = 1.8\text{ nF}$ | | 4 | 7 | ns |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. All Limits are 100% tested at $T_{AMB} = 25^\circ C$ and guaranteed across temperature by design and statistical analysis.
2. Guaranteed by characterization. *See timing Waveforms.

Table 3. LOGIC TRUTH TABLE

| IN+ | IN- | OUTH | OUTL | OUT (OUTH & OUTL CONNECTED TOGETHER) |
|-----|-----|--------|--------|-----------------------------------------|
| L | L | HIGH-Z | L | L |
| L | H | HIGH-Z | L | L |
| H | L | H | HIGH-Z | H |
| H | H | HIGH-Z | L | L |




Figure 3. Non-inverting Input Driver Operation




Figure 4. Inverting Input Driver Operation

NCP81074A, NCP81074B

TYPICAL CHARACTERISTICS




Figure 5. Supply Current vs. Switching Frequency, $V_{DD} = 12\text{ V}$




Figure 6. Supply Current vs. Switching Frequency, $V_{DD} = 4.5\text{ V}$




Figure 7. Fall Time vs. Temperature
 $C_{LOAD} = 1.8\text{ nF}$




Figure 8. Rise Time vs. Temperature
 $C_{load} = 1.8\text{ nF}$




Figure 9. Propagation Delay T_{D1} vs. Supply Voltage




Figure 10. Propagation Delay T_{D2} vs. Supply Voltage

TYPICAL CHARACTERISTICS




Figure 11. Supply Current vs. Supply Voltage
 $C_{LOAD} = 2.2 \text{ nF}$




Figure 12. Supply Current vs. Supply Voltage
 $C_{LOAD} = 4.7 \text{ nF}$




Figure 13. Reverse Current, $P_{MOS(on)}$, $P_{MOS(off)}$




Figure 14. Reverse Current, $P_{MOS(off)}$, $P_{MOS(on)}$




Figure 15. Supply Current vs. Supply Voltage

NCP81074A, NCP81074B

BENCH WAVEFORMS – Non-Inverting Input




Figure 16. Rise Time with 1.8 nF Load




Figure 17. Fall Time with 1.8 nF Load




Figure 18. Propagation Delays with 1.8 nF Load




Figure 19. Propagation Delays with 1.8 nF Load

NCP81074A, NCP81074B

BENCH WAVEFORMS – Inverting Input




Figure 20. Rise Time with 1.8 nF Load




Figure 21. Fall Time with 1.8 nF Load




Figure 22. Propagation Delays with 1.8 nF Load




Figure 23. Propagation Delays with 1.8 nF Load

NCP81074A, NCP81074B

PCB LAYOUT RECOMMENDATION

Proper component placement is extremely important in high current, fast switching applications to provide appropriate device operation and design robustness. The NCP81074 gate driver exhibits a powerful output stage enabling large peak currents with fast rise and fall times. Eventhough the NCP81074 provides a split output configuration for slew rate control, a proper PCB layout is crucial to ensure maximum performance. The following circuit layout guidelines are strongly recommended when designing with the NCP81074.

- Place the driver close to the power MOSFET in order to have a low impedance path between the output pins and the gate. Keep the traces short and wide to minimize the parasitic inductance and accommodate for high peak currents.
- Place the decoupling capacitor close to the gate drive IC. Placing the VDD capacitor close to the pin and ground improves noise filtering. This capacitor supplies

high peak currents during the turn-on transition of the MOSFET. Using a low ESL chip capacitor is highly recommended.

- Keep a tight turn-on turn-off current loop paths to minimize parastic inductance. High di/dt will induce voltage spikes on the output pin and the MOSFET gate. Parallel the source and return signals taking advantage of flux cancellation.
- Since the NCP81074 is a 2x2mm package driving high peak currents into capacitive loads, adding a shielding ground plane helps in power dissipation and noise blocking. The ground plane should not be a current carrying path to any of the current loops.
- Any unused pin, should be pulled to either rail depending on the functionality of the pin to avoid any malfunction on the output. Please refer to the pin description table for more information.









Figure 24.

NCP81074A, NCP81074B

PACKAGE DIMENSIONS


DFN8 2x2
CASE 506AA
ISSUE E



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
 2. CONTROLLING DIMENSION: MILLIMETERS.
 3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.20 MM FROM TERMINAL TIP.
 4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

| MILLIMETERS | | |
|-------------|------|------|
| DIM | MIN | MAX |
| A | 0.80 | 1.00 |
| A1 | 0.00 | 0.05 |
| A3 | 0.20 | REF |
| b | 0.20 | 0.30 |
| D | 2.00 | BSC |
| D2 | 1.10 | 1.30 |
| E | 2.00 | BSC |
| E2 | 0.70 | 0.90 |
| e | 0.50 | BSC |
| K | 0.30 | REF |
| L | 0.25 | 0.35 |
| L1 | — | 0.10 |

RECOMMENDED SOLDERING FOOTPRINT*




DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NCP81074A, NCP81074B

PACKAGE DIMENSIONS

SOIC-8 NB CASE 751-07 ISSUE AK




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.80 | 5.00 | 0.189 | 0.197 |
| B | 3.80 | 4.00 | 0.150 | 0.157 |
| C | 1.35 | 1.75 | 0.053 | 0.069 |
| D | 0.33 | 0.51 | 0.013 | 0.020 |
| G | 1.27 BSC | | 0.050 BSC | |
| H | 0.10 | 0.25 | 0.004 | 0.010 |
| J | 0.19 | 0.25 | 0.007 | 0.010 |
| K | 0.40 | 1.27 | 0.016 | 0.050 |
| M | 0° | 8° | 0° | 8° |
| N | 0.25 | 0.50 | 0.010 | 0.020 |
| S | 5.80 | 6.20 | 0.228 | 0.244 |

SOLDERING FOOTPRINT*



SCALE 6:1 (mm/inches)

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and the are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marketing.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative