imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SOCKETS



SOCKETS						
Product		Features	Accessory For			
OT08PC Octal Socket 8-Pin	BEE • •	8-pin 35mm DIN rail or surface mount octal socket. Rated at 10A @ 600VAC and has pressure clamp terminals.	AWG 12 to 22 (3.2 to 0.33 mm²) wire sizes. Consult individual datasheet for compatibility			
NDS-8 Octal Socket 8-Pin Screw terminals with captive wire clamps		8-pin 35mm DIN rail or surface mount octal socket. Rated at 10A @ 300VAC. Surface mounted with two #6 (M 3.5 x 0.6) screws or snaps onto a 35 mm DIN rail. A spring mechanism allows easy removal. Uses PSC8 hold-down clips.		vo #14 AV n ²) wire s TDB TDIH TDIH TDMH TDSH TRS		LLC5 TDBL TDM TDR TRDU
P1011-6 Octal Socket 8-Pin		8-pin surface mount socket with binder head screw terminals. Rated at 10A @ 600VAC. UL Listed combination when used with TDM, TDB, TDS Series timers. Uses PSCRB8 hold-down brackets.	Series: ARP PRLM TDR TRM	FS500 TDB TDS TRS	LLC4 TDM TRB TRU	LLC5 TDMB TRDU
OT11PC Magnal Socket 11-Pin		Magnal Sockets are for plug-in units	11-pin F Series: ARP TDBL TDSL TRS	Plug-in ur LLC6 TDMB TRB TRU	nits TDB TDS TRDU	TDBH TDSH TRM
SD12-PC Rectangle Socket 12-pin	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	12-pin surface Rectangle Socket.	ACBC-120			
NDS-11 11-pin Magnal Socket Screw terminals with captive wire clamps		11 pin 35 mm DIN rail or surface mount socket. Rated at 10A @ 300VAC. Surface mounted with two #6 (M 3.5 x 0.6) screws or snaps onto a 35 mm DIN rail. A spring mechanism allows easy removal. Uses PSC11 hold-down clips.	AWG 12 (3.2 to 0 Series: ARP TDBL TDSL TRS	.33 mm²)	wire size TDB TDS TRDU	es TDBH TDSH TRM