imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






16-Port 10/100/1000 Mbps 1U Rack-Mount/Desktop Gigabit Ethernet Unmanaged Switch, Metal Housing

MODEL NUMBER: NG16







Energy-efficient unmanaged switch sets up in seconds with no configuration required. Provides a Gigabit network connection for multiple devices. Ideal for home or small offices, workgroups and creative production environments.

Description

The NG16 16-Port 10/100/1000 Mbps 1U Rack-Mount/Desktop Gigabit Ethernet Unmanaged Switch adds 10/100/1000 Mbps Ethernet capacity to your home office, small office, workgroup or creative production environment. Share large bandwidth-intensive files, such as CAD drawings and videos, at Gigabit speeds, improving efficiency and cutting costly downtime.

This rack-mount/desktop switch features 16 twisted-pair RJ45 Gigabit Ethernet ports that support autonegotiable 10/100/1000 Mbps and auto MDI/MDIX cross-over detection functions for convenient plug-andplay capability. No configuration is required, so you can have your Gigabit network up and running immediately. Easy-to-read LEDs indicate connection and activity status for each port. IEEE 802.3x flow control allows smooth transmission of large files.

The NG16 supports IEEE 802.3az Energy Efficient Ethernet standards by putting unused ports into a lowpower state without interrupting network connections. It consumes very little input power—just seven watts max. The detachable five-foot input cord with NEMA 5-15P plug connects to a protected UPS, generator or mains input AC source. The heavy-duty metal housing is designed for desktop installation or mounting into 1U of an EIA-standard 19-inch rack with the included brackets.

Features

Unmanaged Network Switch for Home/Small Offices or Workgroups

• 16 twisted-pair RJ45 Gigabit Ethernet ports

Highlights

- 16 auto-negotiable 10/100/1000
 Mbps RJ45 ports
- Supports auto MDI/MDIX crossover function
- Consumes very little input power—just 7W max
- 2 Gbps switching capacity per port with full duplex
- Plug-and-play with no configuration required

Package Includes

- NG16 16-Port 10/100/1000
 Mbps 1U Rack-Mount/Desktop
 Gigabit Ethernet Unmanaged
 Switch
- Detachable AC power cord with NEMA 5-15P plug, 5 ft.
- (2) Mounting brackets
- (8) Screws
- (4) Rubber feet
- Owner's manual



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

- Auto-negotiable 10/100/1000 Mbps
- Automatic MDI/MDIX cross-over detection
- 32 Gbps switching capacity (2 Gbps per port with full duplex)
- Easy-to-read LEDs indicate connection and activity status for each port
- Supports 9k jumbo frames
- Supports MAC address auto-learning and auto-aging
- Supports 802.3x flow control (full duplex) and back pressure (half duplex)

Compliant with IEEE 802.3az Energy Efficient Ethernet Standards

- · Automatically shifts unused ports to low-power state without interrupting network connection
- Consumes very little input power—just 7W max
- Also meets IEEE 802.3ab, 802.3i, 802.3u and 802.3 standards

Heavy-Duty Metal Housing

- Fanless design for silent operation
- Detachable 5 ft. AC power cord with NEMA 5-15P plug
- Plug-and-play—no configuration necessary

Versatile Installation Options

- Includes rubber feet for secure placement on flat desktop surface
- Mounts in 1U of EIA-standard 19 in. rack with included brackets
- Grounding lug included

Specifications

OVERVIEW		
UPC Code	037332194725	
INPUT		
Electrical Consumption	Up to 7 watts	
Nominal Input Voltage Description	Accepts 100-240V AC nominal input	
Plug Type	Includes NEMA 5-15P input plug	
Input Cord Length (ft.)	5	
Input Cord Length (m)	1.52	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Power LED (Green for Power On); One LED per RJ-45 port (Green indicates 10/100Mbps link; Amber indicates 1000Mbps link; LEDs flash to indicate port activity)	



PHYSICAL		
Primary Form Factor	Desktop; Rackmount	
Shipping Dimensions (hwd / in.)	3.000 × 9.700 × 17.200	
Shipping Dimensions (hwd / cm)	7.62 x 24.64 x 43.69	
Shipping Weight (lbs.)	4.9000	
Shipping Weight (kg)	2.22	
Unit Dimensions (hwd / in.)	1.74 x 11.02 x 7.09	
Unit Dimensions (hwd / cm)	4.42 x 27.99 x 18.01	
Unit Weight (lbs.)	3.2	
Unit Weight (kg)	1.45	
Color	Black	
Form Factors Supported	Desktop, Rackmount	
ENVIRONMENTAL		
Storage Temperature Range	-40 to 158F (-40 to 70C)	
Relative Humidity	10 to 90% (non-condensing)	
Operating Temperature	32 to 104F (0 to 40C)	
CONNECTIONS		
Network Switch Ports	(16) 10/100/1000 (RJ45)	
CERTIFICATIONS		
Certifications	Compliant Standards: IEEE 802.3ab (1000BASE-T GIGABIT ETHERNET), IEEE 802.3i (10BASE-T ETHERNET), IEEE 802.3u (100BASE-T ETHERNET), IEEE 802.3x (FULL DUPLEX/FLOW CONTROL), IEEE 802.3 (NWAY AUTO-NEGOTIATION), 802.3az (ENERGY EFFICIENT ETHERNET)	
Approvals	Tested to North American safety and EMI standards UL60950-1: 2007 (2ND ED) +A1+A2 R14; CAN/CSA C22.2 NO. 60950-1-07, 2ND EDITION, 2014-10; FCC Class B; RoHS Compliant	
WARRANTY		
Product Warranty Period (Worldwide)	5-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies