



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



▶▶▶ Configuration Recovery Option

NTCD-128 Configuration Recovery Option

Available for N-Tron products
with SD backup feature



Time Saving Assistance

The N-Tron® NTCD-128 Recovery Backup Option allows backup of stored data, saving valuable configuration time. Unlike ordinary SD cards, the NTCD-128 is formatted specifically for N-Tron products and is rated for industrial use, including operation in extreme temperatures. Backup includes stored settings for:

- IP address, subnet mask, and gateway
- User names and passwords
- Administrative and user management
- Port settings
- N-Ring
- N-Link
- N-View OPC Server
- Rate limiting
- RSTP
- VLAN
- IGMP
- DHCP client and relay
- Trunking
- Mirroring
- QoS
- LLDP
- Unicast and multicast filters
- CIP
- SNMP trap
- MAC security
- Fault configuration
- Aging

ORDERING INFORMATION

PART NUMBER	DESCRIPTION
NTCD-128	128 MB SD Card for configuration recovery (-40°C to 85°C operating temperature)

