mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Power MOSFET

-8.0 V, -7.5 A P-Channel ChipFET™

Features

- Offers an Ultra Low R_{DS(on)} Solution in the ChipFET Package
- Miniature ChipFET Package 40% Smaller Footprint than TSOP-6 making it an Ideal Device for Applications where Board Space is at a Premium
- Low Profile (<1.1 mm) Allows it to Fit Easily into Extremely Thin Environments such as Portable Electronics
- Designed to Provide Low R_{DS(on)} at Gate Voltage as Low as 1.8 V, the Operating Voltage used in many Logic ICs in Portable Electronics
- Simplifies Circuit Design since Additional Boost Circuits for Gate Voltages are not Required
- Operated at Standard Logic Level Gate Drive, Facilitating Future Migration to Lower Levels using the same Basic Topology
- Pb–Free Package is Available

Applications

- Optimized for Battery and Load Management Applications in Portable Equipment such as MP3 Players, Cell Phones, Digital Cameras, Personal Digital Assistant and other Portable Applications
- Charge Control in Battery Chargers
- Buck and Boost Converters

MAXIMUM RATINGS (T_J = 25° C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	-8.0	V _{dc}
Gate-to-Source Voltage - Continuous	V _{GS}	±8.0	V _{dc}
Drain Current – Continuous – 5 seconds	I _D	-5.4 -7.5	A
Total Power Dissipation Continuous @ $T_A = 25^{\circ}C$ (5 sec) @ $T_A = 25^{\circ}C$ Continuous @ $85^{\circ}C$ (5 sec) @ $85^{\circ}C$	P _D	1.3 2.5 0.7 1.3	W
Continuous Source Current	ls	-1.1	А
Thermal Resistance (Note 1) Junction-to-Ambient, 5 sec Junction-to-Ambient, Continuous	$R_{\theta J A}$	50 95	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 10 seconds	ΤL	260	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. Surface Mounted on FR4 Board using 1 in sq pad size (Cu area = 1.27 in sq [1 oz] including traces).



ON Semiconductor®

http://onsemi.com

V _{(BR)DSS}	Ultra Low R _{DS(on)} TYP	I _D MAX
	19 m Ω @ –4.5 V $_{ m GS}$	
–8.0 V	25 mΩ @ –2.5 V _{GS}	–7.5 A
	34 mΩ @ –1.8 V _{GS}	



P-Channel MOSFET



ChipFET CASE 1206A STYLE 1



D4 = Specific Device Code M = Month Code

ORDERING INFORMATION

Device	Package	Shipping [†]		
NTHS2101PT1	ChipFET	3000/Tape & Reel		
NTHS2101PT1G	ChipFET (Pb–Free)	3000/Tape & Reel		

+For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

ELECTRICAL CHARACTERISTICS (T_J = 25° C unless otherwise noted)

Characteristic	Symbol	Test Condition	Min	Тур	Max	Unit
OFF CHARACTERISTICS						
Drain-to-Source Breakdown Voltage (Note 2) Temperature Coefficient (Positive)	V _{(Br)DSS}	$V_{GS}=0~V_{dc},~I_D=-250~\mu A_{dc}$	-8.0			V _{dc}
Gate-Body Leakage Current Zero	I _{GSS}	$V_{DS} = 0 V_{dc}, V_{GS} = \pm 8.0 V_{dc}$			±100	nA _{dc}
Zero Gate Voltage Drain Current	I _{DSS}	$ \begin{array}{l} {\sf V}_{DS} = -6.4 \; {\sf V}_{dc}, \; {\sf V}_{GS} = 0 \; {\sf V}_{dc} \\ {\sf V}_{DS} = -6.4 \; {\sf V}_{dc}, \; {\sf V}_{GS} = 0 \; {\sf V}_{dc}, \\ {\sf T}_J = 85^\circ C \end{array} $			-1.0 -5.0	μA _{dc}
ON CHARACTERISTICS (Note 2)					•	
Gate Threshold Voltage	V _{GS(th)}	V_{DS} = V_{GS} , I_D = -250 μA_{dc}	-0.45		-1.5	V _{dc}
Static Drain-to-Source On-Resistance	R _{DS(on)}	$\begin{array}{l} V_{GS} = -4.5 \; V_{dc}, \; I_D = -5.4 \; A_{dc} \\ V_{GS} = -2.5 \; V_{dc}, \; I_D = -4.5 \; A_{dc} \\ V_{GS} = -1.8 \; V_{dc}, \; I_D = -2.0 \; A_{dc} \end{array}$		19 25 34	25 36 48	mΩ
Forward Transconductance	9 FS	$V_{DS} = -5.0 V_{dc}, I_D = -5.2 A_{dc}$		20		S
Diode Forward Voltage	V _{SD}	$I_{S} = -1.1 \ A_{dc}, \ V_{GS} = 0 \ V_{dc}$		-0.62	-1.2	V
DYNAMIC CHARACTERISTIC						
Input Capacitance	C _{iss}	$V_{DS} = -6.4 V_{dc}$		2400		pF
Output Capacitance	C _{oss}	V _{GS} = 0 V f = 1.0 MHz		550		
Transfer Capacitance	C _{rss}	1 = 1.0 With Z		420		
SWITCHING CHARACTERISTICS (Note 3)						
Turn-On Delay Time	t _{d(on)}	$V_{DD} = -6.4 V_{dc}$		7.0		ns
Rise Time	t _r	$V_{GS} = -4.5 V_{dc}$		28		
Turn–Off Delay Time	t _{d(off)}	$R_{G} = 2.0 \Omega$ (Note 2)		73		
Fall Time	t _f			60		
Gate Charge	Q _G	$V_{GS} = -4.5 V_{dc}$		15	30	nC
Q _{GS}	$I_D = -5.4 A_{dc}$		4.0			
	Q_{GD} $V_{DS} = -6.4 V_{dc}$	$V_{DS} = -6.4 V_{dc}$		8.0		
Source-Drain Reverse Recovery Time	T _{rr}	I _F = −1.1 A, di/dt = 100 A/μs		90		ns

Pulse Test: Pulse Width = 250 μs, Duty Cycle = 2%.
 Switching characteristics are independent of operating junction temperatures.

TYPICAL ELECTRICAL CHARACTERISTICS



TYPICAL ELECTRICAL CHARACTERISTICS





PACKAGE DIMENSIONS









- NOTES: 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982. 2. CONTROLLING DIMENSION: MILLIMETER. 3. MOLD GATE BURRS SHALL NOT EXCEED 0.13 MM
- WIDD GATE DURING SHALL NOT EXCEED U.13 MIM PER SIDE.
 LEADFRAME TO MOLDED BODY OFFSET IN HORIZONTAL AND VERTICAL SHALL NOT EXCEED 0.08 MM.
- U.U.B MM.
 DIMENSIONS A AND B EXCLUSIVE OF MOLD GATE BURRS.
 NO MOLD FLASH ALLOWED ON THE TOP AND BOTTOM LEAD SURFACE.
 1206A-01 AND 1206A-02 OBSOLETE. NEW STANDARD IS 1206A-03.

	MILLIN	IETERS	INCHES		
DIM	MIN	MAX	MIN	MAX	
Α	2.95	3.10	0.116	0.122	
В	1.55	1.70	0.061	0.067	
C	1.00	1.10	0.039	0.043	
D	0.25	0.35	0.010	0.014	
G	0.65	5 BSC	0.025 BSC		
J	0.10	0.20	0.004	0.008	
K	0.28	0.42	0.011	0.017	
L	0.55 BSC		0.022 BSC		
М	5 ° NOM		5 ° NOM		
S	1.80	2.00	0.072 0.08		

SOLDERING FOOTPRINTS*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ChipFET is a trademark of Vishay Siliconix.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use persons. All easys negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunit/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor P.O. Box 61312, Phoenix, Arizona 85082–1312 USA Phone: 480–829–7710 or 800–344–3860 Toll Free USA/Canada Fax: 480–829–7709 or 800–344–3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center 2–9–1 Kamimeguro, Meguro–ku, Tokyo, Japan 153–0051 Phone: 81–3–5773–3850 ON Semiconductor Website: http://onsemi.com

Order Literature: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.

NTHS2101P/D