



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# NTK3043N

## Power MOSFET

20 V, 285 mA, N-Channel with ESD Protection, SOT-723

### Features

- Enables High Density PCB Manufacturing
- 44% Smaller Footprint than SC-89 and 38% Thinner than SC-89
- Low Voltage Drive Makes this Device Ideal for Portable Equipment
- Low Threshold Levels,  $V_{GS(TH)} < 1.3$  V
- Low Profile (< 0.5 mm) Allows It to Fit Easily into Extremely Thin Environments such as Portable Electronics
- Operated at Standard Logic Level Gate Drive, Facilitating Future Migration to Lower Levels Using the Same Basic Topology
- These are Pb-Free and Halogen Free Devices

### Applications

- Interfacing, Switching
- High Speed Switching
- Cellular Phones, PDAs

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise stated)

Parameter		Symbol	Value	Unit	
Drain-to-Source Voltage		$V_{DSS}$	20	V	
Gate-to-Source Voltage		$V_{GS}$	$\pm 10$	V	
Continuous Drain Current (Note 1)	Steady State	$I_D$	$T_A = 25^\circ\text{C}$	255	mA
			$T_A = 85^\circ\text{C}$	185	
	$t \leq 5$ s	$T_A = 25^\circ\text{C}$	285		
Power Dissipation (Note 1)	Steady State	$P_D$	$T_A = 25^\circ\text{C}$	440	mW
				$t \leq 5$ s	
Continuous Drain Current (Note 2)	Steady State	$I_D$	$T_A = 25^\circ\text{C}$	210	mA
			$T_A = 85^\circ\text{C}$	155	
			$T_A = 25^\circ\text{C}$	310	
Power Dissipation (Note 2)		$P_D$			mW
Pulsed Drain Current	$t_p = 10 \mu\text{s}$	$I_{DM}$	400	mA	
Operating Junction and Storage Temperature		$T_J, T_{STG}$	-55 to 150	$^\circ\text{C}$	
Source Current (Body Diode) (Note 2)		$I_S$	286	mA	
Lead Temperature for Soldering Purposes (1/8" from case for 10 seconds)		$T_L$	260	$^\circ\text{C}$	

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Surface-mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces)
2. Surface-mounted on FR4 board using the minimum recommended pad size.




ON Semiconductor®

<http://onsemi.com>


$V_{(BR)DSS}$	$R_{DS(on)}$ TYP	$I_D$ Max
20 V	1.5 $\Omega$ @ 4.5 V	285 mA
	2.4 $\Omega$ @ 2.5 V	
	5.1 $\Omega$ @ 1.8 V	
	6.8 $\Omega$ @ 1.65 V	

Top View




- 1 – Gate
- 2 – Source
- 3 – Drain

### MARKING DIAGRAM



SOT-723  
CASE 631AA  
STYLE 5



KA = Device Code  
M = Date Code

### ORDERING INFORMATION

Device	Package	Shipping†
NTK3043NT1G	SOT-723*	4000 / Tape & Reel
NTK3043NT5G	SOT-723*	8000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

\*These packages are inherently Pb-Free.

# NTK3043N

## THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
Junction-to-Ambient – Steady State (Note 3)	$R_{\theta JA}$	280	°C/W
Junction-to-Ambient – $t = 5$ s (Note 3)	$R_{\theta JA}$	228	
Junction-to-Ambient – Steady State Minimum Pad (Note 4)	$R_{\theta JA}$	400	

3. Surface-mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces)

4. Surface-mounted on FR4 board using the minimum recommended pad size.

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Test Condition	Symbol	Min	Typ	Max	Unit
-----------	----------------	--------	-----	-----	-----	------

### OFF CHARACTERISTICS

Drain-to-Source Breakdown Voltage	$V_{GS} = 0$ V, $I_D = 100$ $\mu$ A	$V_{(BR)DSS}$	20			V
Drain-to-Source Breakdown Voltage Temperature Coefficient	$I_D = 100$ $\mu$ A, Reference to $25^\circ\text{C}$	$V_{(BR)DSS}/T_J$		27		mV/°C
Zero Gate Voltage Drain Current	$V_{GS} = 0$ V, $V_{DS} = 16$ V	$I_{DSS}$	$T_J = 25^\circ\text{C}$		1	$\mu$ A
			$T_J = 125^\circ\text{C}$		10	
Gate-to-Source Leakage Current	$V_{DS} = 0$ V, $V_{GS} = \pm 5$ V	$I_{GSS}$			1	$\mu$ A

### ON CHARACTERISTICS (Note 3)

Gate Threshold Voltage	$V_{GS} = V_{DS}$ , $I_D = 250$ $\mu$ A	$V_{GS(TH)}$	0.4		1.3	V
Gate Threshold Temperature Coefficient		$V_{GS(TH)}/T_J$		-2.4		mV/°C
Drain-to-Source On Resistance	$V_{GS} = 4.5$ V, $I_D = 10$ mA	$R_{DS(ON)}$		1.5	3.4	$\Omega$
			$V_{GS} = 4.5$ V, $I_D = 255$ mA	1.6	3.8	
			$V_{GS} = 2.5$ V, $I_D = 1$ mA	2.4	4.5	
			$V_{GS} = 1.8$ V, $I_D = 1$ mA	5.1	10	
			$V_{GS} = 1.65$ V, $I_D = 1$ mA	6.8	15	
Forward Transconductance	$V_{DS} = 5$ V, $I_D = 100$ mA	$g_{FS}$		0.275		S

### CHARGES, CAPACITANCES AND GATE RESISTANCE

Input Capacitance	$V_{GS} = 0$ V, $f = 1$ MHz, $V_{DS} = 10$ V	$C_{ISS}$		11		pF
Output Capacitance		$C_{OSS}$		8.3		
Reverse Transfer Capacitance		$C_{RSS}$		2.7		

### SWITCHING CHARACTERISTICS, $V_{GS} = 4.5$ V (Note 4)

Turn-On Delay Time	$V_{GS} = 4.5$ V, $V_{DD} = 5$ V, $I_D = 10$ mA, $R_G = 6$ $\Omega$	$t_{d(ON)}$		13		ns
Rise Time		$t_r$		15		
Turn-Off Delay Time		$t_{d(OFF)}$		94		
Fall Time		$t_f$		55		

### DRAIN-SOURCE DIODE CHARACTERISTICS

Forward Diode Voltage	$V_{GS} = 0$ V, $I_S = 286$ mA	$T_J = 25^\circ\text{C}$	$V_{SD}$	0.83	1.2	V
		$T_J = 125^\circ\text{C}$		0.69		
Reverse Recovery Time	$V_{GS} = 0$ V, $V_{DD} = 20$ V, $dI_{SD}/dt = 100$ A/ $\mu$ s, $I_S = 286$ mA	$t_{RR}$		9.1		ns
Charge Time		$t_a$		7.1		
Discharge Time		$t_b$		2.0		
Reverse Recovery Charge		$Q_{RR}$		3.7		

5. Pulse Test: pulse width  $\leq 300$   $\mu$ s, duty cycle  $\leq 2\%$

6. Switching characteristics are independent of operating junction temperatures

TYPICAL PERFORMANCE CURVES




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature






Figure 6. Drain-to-Source Leakage Current vs. Voltage

# NTK3043N


## TYPICAL PERFORMANCE CURVES



**Figure 7. Capacitance Variation**



**Figure 8. Resistive Switching Time Variation vs. Gate Resistance**




**Figure 9. Diode Forward Voltage vs. Current**

# NTK3043N

## PACKAGE DIMENSIONS

**SOT-723**  
CASE 631AA  
ISSUE D



**NOTES:**


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	0.45	0.50	0.55
b	0.15	0.21	0.27
b1	0.25	0.31	0.37
C	0.07	0.12	0.17
D	1.15	1.20	1.25
E	0.75	0.80	0.85
e	0.40 BSC		
H E	1.15	1.20	1.25
L	0.29 REF		
L2	0.15	0.20	0.25

**STYLE 5:**

1. GATE
2. SOURCE
3. DRAIN

### RECOMMENDED SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative