



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Integrated Device Technology

The Analog and Digital Company™



[Products](#) | [Applications](#) | [Search](#) | [Support](#) | [Investor](#) | [About IDT](#)

[Telecommunication ICs](#) [Voice Processing](#) [Caller ID](#) [NW6005](#) [NW6005ASG](#)

NW6005ASG

[Description](#) | [Parameters](#) | [Package](#) | [Documents](#) | [Distributor Inventory](#) | [Contacts](#)

DESCRIPTION

CALLER ID ENHANCED TYPE I
FSK, CAS, Alerts, Tip/Ring, Hybrid separate Op Amps
Generic Part:
NW6005
Category:
Caller ID

PARAMETERS

Package SOIC 20
Temperature I
Voltage 5.0 V
I/O Voltage
Density
Speed NA

PACKAGE

Package SOIC 20 (PSG20)
Description SOIC 300 MIL
Status Active
Class PLASTIC
Category [Green](#)
Pb (Lead) Free [Yes](#)
Pb Free Category e3 Sn
Mark SOG
Package Type SOIC
Lead Count 20
Length 12.8 mm
Width 7.6 mm
Thickness 2.34 mm
Pitch 1.27 mm
Tube / Tray TUBE
Quantity per Tube/Tray 37
Quantity per Reel 1000
Moisture Sensitivity Level (MSL) 1
Moisture Exposure Floor Life Unlimited@<30C/85% RH
Peak Reflow Temperature 260°C
Rebake Conditions NA
Related Package Documents [view documents](#)

DOCUMENTS

Type	Title	Size	Revision Date
Datasheet	NW6005 Data Sheet	298 KB	07/01/2002
Product Change Notice See More Docs	PCN# : TB0902-01 TRACEABILITY MARK ON TOP OF PACKAGE	1024 KB	03/03/2009
	PCN# A-0504-02R2: Assembly Transfer IDT-Manila to OSE-Ph	39 KB	08/04/2005
	PCN#A-0504-02R1: Assembly Transfer IDT-Manila to OSE-Ph	17 KB	07/22/2005
	PCN#: A-0504-02, Transfer assembly facility IDT-Manila to OSE-Ph	48 KB	04/29/2005
	PCN#: A-0412-04 - To comply with Pb-free labels - Green Products	81 KB	12/14/2004
	PCN#: A-0410-02, Change IDT marking logo with new IDT gridless w	25 KB	10/08/2004
	PCN#:A-0401-01, new m/c G600 & 8290 d/a material	197 KB	01/19/2004
	PCN#: A-0310-01, Green Products	27 KB	10/10/2003
	PCN# G-0203-05 Mold Compound	41 KB	04/16/2002
	PCN# G0202-01, Alternate assembly facility	17 KB	02/08/2002

DISTRIBUTOR INVENTORY

Part	Distributor	Qty	Date	RFQ	Order
No matches found.					

CONTACTS

Sales Offices

- ▶ [Sales Offices and authorized distributors](#)

Technical Support

Telecommunication ICs and Products

- ▶ Email: wireline@idt.com
- ▶ Phone: 408-360-1552
- ▶ Phone: +86 21-64958900 ext. 388 (China/Taiwan)

Copyright © 2011 Integrated Device Technology, Inc. | [Legal](#) | [Careers](#) | [Contact Us](#) | [myIDT](#) | [Press Room](#)