



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## NX3225SA For OA / AV Mobile Communications/ Short-range Wireless

### ■ Features

Ideal for such as bluetooth, Wifi, smartphone and tablet pc.

- Compact and thin. (3.2 × 2.5 × 0.55 mm typ.)
- Excellent environmental characteristics, including heat and shock resistance.
- Lead-free. Meets the requirements for re-flow profiling using lead-free solder.




Pb Free

RoHS Compliant  
Directive 2011/65/EU

### ■ Specifications

Item	Model	NX3225SA		
Nominal Frequency		12 to 64 MHz	16 to 54 MHz	40 to 150 MHz
Overtone Order		Fundamental	Fundamental	3rd overtone
Frequency Tolerance (25 ±3 °C)		±15 × 10 <sup>-6</sup>	±10 × 10 <sup>-6</sup>	±20 × 10 <sup>-6</sup>
Frequency versus Temperature Characteristics (with reference to +25 °C)		±25 × 10 <sup>-6</sup>	±10 × 10 <sup>-6</sup>	±25 × 10 <sup>-6</sup>
Operating Temperature Range		-40 to +85 °C	-20 to +75 °C	-40 to +85 °C
Storage Temperature Range		-40 to +85 °C		
Equivalent Series Resistance		Refer to *1	Refer to *2	Refer to *3
Level of Drive		10 μW (Max. 200 μW)		
Load Capacitance		8 pF	10 pF	Series resonance
Specifications Number		STD-CSR-6	STD-CSQ-1	STD-CSR-7

### ■ Dimensions



#### \*1 Equivalent Series Resistance

Overtone Order	Nominal frequency (MHz)	Equivalent Series Resistance max. [Ω]
Fundamental	12 to 13	100
	13 to 20	80
	20 to 64	50

#### \*2 Equivalent Series Resistance

Overtone Order	Nominal frequency (MHz)	Equivalent Series Resistance max. [Ω]
Fundamental	16 to 20	80
	20 to 54	50

#### \*3 Equivalent Series Resistance

Overtone Order	Nominal frequency (MHz)	Equivalent Series Resistance max. [Ω]
3rd overtone	40 to 100	140
	100 to 150	100

Please specify the model name, frequency, and specification number when you order products.  
For further questions regarding specifications, please feel free to contact us.