

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Specification of Crystal Unit



| 1 | NDK PART NUMBER | NX5032GA (STD-CSU-1)(STD-CSU-2) NX5032GA | |
|--|---|---|--|
| 5 | Туре | 10.000207 | |
| 6 6.1 6.2 | Electrical characteristics Nominal frequency(F0) Overtone order | * ATTACHED SHEETS 3 8MHZ to40MHZ Fundamental | |
| 6.3 | Adjustment tolerance | ±50×10 ⁻⁶ max. (+25 °C) | |
| 6.4 6.5 6.6 6.7 | Tolerance over the temperature range Equivalent resistance (R1) Shunt Capacitance (C0) Motional Capacitance (C1) | $\pm 150\times 10^{-6}$ max. (-40~+150 °C) The reference temperature shall be +25 °C. *ATTACHED SHEETS 3 NA $500\mu W$ max. | |
| 7.1.2 7.1.3 7.2 7.2.1 7.2.2 | Measurement circuit Frequency measurement Measuring instrument Load capacitance(CL) Level of drive Equivalent resistance measurement Measuring instrument Load capacitance(CL) Level of drive | π circuit 8pF 10μW $π$ circuit Series 10μW | |
| 8 | Cover Alumina Ceramics | ±0.2 | |
| | Base Alumina Ceramics | 1.0 ±0.2 | |
| Term in a l 1.3 ± 0.2 Tung sten Metalize (Au plating on Ni pre plating) Au plating (0.3 \sim 1.0 μ m), Ni pre plating (1 \sim 9 μ m) | | | |
| | REFERRENCE LAND PATTERN (TY | | |

| Frequency(MHz) | CI(ESR) |
|----------------|---------|
| 8 | 300 |
| 10 | 120 ohm |
| 12 | 120 ohm |
| 16 | 120 ohm |
| 20 | 70 ohm |
| 40 | 50 ohm |