imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



BLUE/GREEN ENHANCED 6 mm² PHOTODIODE-PREAMPLIFIER

ODA-6WB-100M



FEATURES

- Large active area
- · Low noise
- · High sensitivity
- · Custom gains available
- Hermetically sealed TO-39
- · Blue enhanced detector



R1 $C1$ $U1$ $U1$ $U1$ $U1$ $U1$ $U1$ $U1$ U
--

ELECTRO-OPTICAL CHARACTERISTICS AT 23°C


PARAMETERS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Dark Offset	$V_s = \pm 5 V$		1.2	± 2	mV
Dark Offset Noise	$V_s = \pm 5$		198	250	µV rms
	BW = 0.1 to 1000 Hz				
Sensitivity	$V_s = \pm 5 V$	20	28		V/µW
	$\lambda = 450 \text{ nm}$				
Frequency Response (-3 db)	$V_s = \pm 5 V$	900	1000		Hz
	$\lambda = 940 \text{ nm}$				
NEP	λ = 940 nm		0.08		pW/√Hz
Transimpedence Gain			100		MΩ
Supply Current			850	950	μΑ

THERMAL PARAMETERS

Voltage Supplies	± 5 to ± 15V		
Power Dissipation	30 mW		
Storage and Operating Temperature	–25° to +100° C		
Soldering Temperature (1/16" from case for 3 secconds max)	+260° C		



BLUE/GREEN ENHANCED 6 mm² PHOTODIODE-PREAMPLIFIER





750 Mitchell Road, Newbury Park, California 91320 Phone: (805) 499-0335, Fax: (805) 499-8108 Email: sales@optodiode.com, Website: www.optodiode.com

Revision February 26, 2013