



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Little Rebel®

Carbon Film Resistors, 5% Tolerance
Available in E24 Ohmic values



Little Rebels are one of Ohmite's more economical lines of low wattage resistors. Constructed of a pure carbon film deposited on a high-grade ceramic body, these units offer better stability performance than comparable carbon composition resistors. Little Rebels are designed for electrical and electronic applications that demand small sizes and small power ratings plus high performance and reliability.

FEATURES

- High stability, low noise level, long life.
- Ideal for applications requiring a steady low power drop.
- Available in Resistor Cabinet Assortments.
- 24 Values per decade.

SERIES SPECIFICATIONS

Series	Wattage	Ohms	Max. Working Voltage
OJ	0.125	1.0- 1M	200
OK	0.250	1.0-10M	250
OL	0.500	1.0-10M	350
OM	1.00	1.0-10M	500
ON	2.00	1.0-10M	500


*Available in Cabinet Assortments

CHARACTERISTICS

Core	High-grade ceramic.
Terminals	Solder-coated copper lead.
Derating	Linearly from 100% @ +70°C to 0% @ 155°C.
Tolerance	±5%.
Temperature Coefficient	1Ω to 10: ±350 ppm/°C 11Ω to 91K: -450 ppm/°C 100K to 1M: -700 ppm/°C 1.1M to 10M: -800 to 1500 ppm/°C
Maximum Overload Voltage	OJ: 400 Volts OK: 500 Volts OL: 700 Volts OM: 1000 Volts ON: 1000 Volts
Quantity per reel	OJ: 5000 OK: 5000 OL: 4000 OM: 2500 ON: 1000

DIMENSIONS

(in./mm)



Series	Wattage	Max. Length	Max. Diam.	Lead ga.
OJ	0.125	0.138 / 3.5	0.073 / 1.85	24
OK	0.250	0.268 / 6.8	0.099 / 2.5	22
OL	0.500	0.355 / 9.0	0.118 / 3.0	22
OM	1.00	0.473 / 12.0	0.197 / 5.0	20
ON	2.00	0.630 / 16.0	0.217 / 5.5	20

(continued)

Little Rebel®

Carbon Film Resistors, 5% Tolerance Available in E24 Ohmic values

ORDERING INFORMATION

Standard part numbers for standard resistance values

Ohmic value	Part No. Prefix Suffix	Wattage 0.125 0.25 0.50 1.0 2.0	Ohmic value	Part No. Prefix Suffix	Wattage 0.125 0.25 0.50 1.0 2.0	Ohmic value	Part No. Prefix Suffix	Wattage 0.125 0.25 0.50 1.0 2.0	Ohmic value	Part No. Prefix Suffix	Wattage 0.125 0.25 0.50 1.0 2.0
1	—10G5	✓✓✓✓✓	62	—6205	✓✓✓✓✓	3,900	—3925	✓✓✓✓✓	240,000	—2445	✓✓✓✓✓
1.1	—11G5	✓✓✓✓✓	68	—6805	✓✓✓✓✓	4,300	—4325	✓✓✓✓✓	270,000	—2745	✓✓✓✓✓
1.2	—12G5	✓✓✓✓✓	75	—7505	✓✓✓✓✓	4,700	—4725	✓✓✓✓✓	300,000	—3045	✓✓✓✓✓
1.3	—13G5	✓✓✓✓✓	82	—8205	✓✓✓✓✓	5,100	—5125	✓✓✓✓✓	330,000	—3345	✓✓✓✓✓
1.5	—15G5	✓✓✓✓✓	91	—9105	✓✓✓✓✓	5,600	—5625	✓✓✓✓✓	360,000	—3645	✓✓✓✓✓
1.6	—16G5	✓✓✓✓✓	100	—1015	✓✓✓✓✓	6,200	—6225	✓✓✓✓✓	390,000	—3945	✓✓✓✓✓
1.8	—18G5	✓✓✓✓✓	110	—1115	✓✓✓✓✓	6,800	—6825	✓✓✓✓✓	430,000	—4345	✓✓✓✓✓
2.0	—20G5	✓✓✓✓✓	120	—1215	✓✓✓✓✓	7,500	—7525	✓✓✓✓✓	470,000	—4745	✓✓✓✓✓
2.2	—22G5	✓✓✓✓✓	130	—1315	✓✓✓✓✓	8,200	—8225	✓✓✓✓✓	510,000	—5145	✓✓✓✓✓
2.4	—24G5	✓✓✓✓✓	150	—1515	✓✓✓✓✓	9,100	—9125	✓✓✓✓✓	560,000	—5645	✓✓✓✓✓
2.7	—27G5	✓✓✓✓✓	160	—1615	✓✓✓✓✓	10,000	—1035	✓✓✓✓✓	620,000	—6245	✓✓✓✓✓
3.0	—30G5	✓✓✓✓✓	180	—1815	✓✓✓✓✓	11,000	—1135	✓✓✓✓✓	680,000	—6845	✓✓✓✓✓
3.3	—33G5	✓✓✓✓✓	200	—2015	✓✓✓✓✓	12,000	—1235	✓✓✓✓✓	750,000	—7545	✓✓✓✓✓
3.6	—36G5	✓✓✓✓✓	220	—2215	✓✓✓✓✓	13,000	—1335	✓✓✓✓✓	820,000	—8245	✓✓✓✓✓
3.9	—39G5	✓✓✓✓✓	240	—2415	✓✓✓✓✓	15,000	—1535	✓✓✓✓✓	910,000	—9145	✓✓✓✓✓
4.3	—43G5	✓✓✓✓✓	270	—2715	✓✓✓✓✓	16,000	—1635	✓✓✓✓✓	1 MEG	—1055	✓✓✓✓✓
4.7	—47G5	✓✓✓✓✓	330	—3315	✓✓✓✓✓	18,000	—1835	✓✓✓✓✓	1.1 MEG	—1155	✓✓✓✓✓
5.1	—51G5	✓✓✓✓✓	350	—3515	✓✓✓✓✓	20,000	—2035	✓✓✓✓✓	1.2 MEG	—1255	✓✓✓✓✓
5.6	—56G5	✓✓✓✓✓	360	—3615	✓✓✓✓✓	22,000	—2235	✓✓✓✓✓	1.3 MEG	—1355	✓✓✓✓✓
6.2	—62G5	✓✓✓✓✓	390	—3915	✓✓✓✓✓	24,000	—2435	✓✓✓✓✓	1.5 MEG	—1555	✓✓✓✓✓
6.8	—68G5	✓✓✓✓✓	430	—4315	✓✓✓✓✓	27,000	—2735	✓✓✓✓✓	1.6 MEG	—1655	✓✓✓✓✓
7.5	—75G5	✓✓✓✓✓	470	—4715	✓✓✓✓✓	30,000	—3035	✓✓✓✓✓	1.8 MEG	—1855	✓✓✓✓✓
8.2	—82G5	✓✓✓✓✓	510	—5115	✓✓✓✓✓	33,000	—3335	✓✓✓✓✓	2.0 MEG	—2055	✓✓✓✓✓
9.1	—91G5	✓✓✓✓✓	560	—5615	✓✓✓✓✓	36,000	—3635	✓✓✓✓✓	2.2 MEG	—2255	✓✓✓✓✓
10	—1005	✓✓✓✓✓	620	—6215	✓✓✓✓✓	39,000	—3935	✓✓✓✓✓	2.4 MEG	—2455	✓✓✓✓✓
11	—1105	✓✓✓✓✓	680	—6815	✓✓✓✓✓	43,000	—4335	✓✓✓✓✓	2.7 MEG	—2755	✓✓✓✓✓
12	—1205	✓✓✓✓✓	750	—7515	✓✓✓✓✓	47,000	—4735	✓✓✓✓✓	3.0 MEG	—3055	✓✓✓✓✓
13	—1305	✓✓✓✓✓	820	—8215	✓✓✓✓✓	51,000	—5135	✓✓✓✓✓	3.3 MEG	—3355	✓✓✓✓✓
15	—1505	✓✓✓✓✓	910	—9115	✓✓✓✓✓	56,000	—5635	✓✓✓✓✓	3.6 MEG	—3655	✓✓✓✓✓
16	—1605	✓✓✓✓✓	1,000	—1025	✓✓✓✓✓	62,000	—6235	✓✓✓✓✓	3.9 MEG	—3955	✓✓✓✓✓
18	—1805	✓✓✓✓✓	1,100	—1125	✓✓✓✓✓	68,000	—6835	✓✓✓✓✓	4.3 MEG	—4355	✓✓✓✓✓
20	—2005	✓✓✓✓✓	1,200	—1225	✓✓✓✓✓	75,000	—7535	✓✓✓✓✓	4.7 MEG	—4755	✓✓✓✓✓
22	—2205	✓✓✓✓✓	1,300	—1325	✓✓✓✓✓	82,000	—8235	✓✓✓✓✓	5.1 MEG	—5155	✓✓✓✓✓
24	—2405	✓✓✓✓✓	1,500	—1525	✓✓✓✓✓	91,000	—9135	✓✓✓✓✓	5.6 MEG	—5655	✓✓✓✓✓
27	—2705	✓✓✓✓✓	1,600	—1625	✓✓✓✓✓	100,000	—1045	✓✓✓✓✓	6.2 MEG	—6255	✓✓✓✓✓
30	—3005	✓✓✓✓✓	1,800	—1825	✓✓✓✓✓	110,000	—1145	✓✓✓✓✓	6.8 MEG	—6855	✓✓✓✓✓
33	—3305	✓✓✓✓✓	2,000	—2025	✓✓✓✓✓	120,000	—1245	✓✓✓✓✓	7.5 MEG	—7555	✓✓✓✓✓
36	—3605	✓✓✓✓✓	2,200	—2225	✓✓✓✓✓	130,000	—1345	✓✓✓✓✓	8.2 MEG	—8255	✓✓✓✓✓
39	—3905	✓✓✓✓✓	2,400	—2425	✓✓✓✓✓	150,000	—1545	✓✓✓✓✓	9.1 MEG	—9155	✓✓✓✓✓
43	—4305	✓✓✓✓✓	2,700	—2725	✓✓✓✓✓	160,000	—1645	✓✓✓✓✓	10 MEG	—1065	✓✓✓✓✓
47	—4705	✓✓✓✓✓	3,000	—3025	✓✓✓✓✓	180,000	—1845	✓✓✓✓✓			
51	—5105	✓✓✓✓✓	3,300	—3325	✓✓✓✓✓	200,000	—2045	✓✓✓✓✓			
56	—5605	✓✓✓✓✓	3,600	—3625	✓✓✓✓✓	220,000	—2245	✓✓✓✓✓			

