

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







OMNI®-BP Line Voltage Ultrasonic Ceiling Sensor

CEILING MOUNT OCCUPANCY SENSORS









PROJECT INFORMATION

Project Name

Catalog No.



OMNIUS500BP1277

The OMN/USBP1277 line voltage ceiling sensor uses ultrasonic (US) technology to turn lighting on and off based on occupancy. Designed specifically for both areas with obstructions (e.g. columns, cubicles, stalls, and filing cabinets) and areas with long periods of minor-motion activity (e.g. typing), this sensor features Hubbell Controls' patented IntelliDAPT® technology, which makes all the sensor adjustments automatically.


Throughout the product's lifespan, smart software analyzes the controlled area and makes digital adjustments to sensitivity and timer settings. Occupancy sensors with *IntelliDAPT* technology provide a maintenance-free install-and-forget operation.


PRODUCT FEATURES


- IntelliDAPT self-adaptive technology no manual adjustment required
- Superior all-digital ultrasonic (US) minor motion detection
- Non-volatile memory for sensor settings
- 500-2,000 square-foot coverage area (depending on model)
- · Self-contained power supply
- Universal voltage (120-277VAC; 50/60 Hz)
- UL and cUL listed
- · California Title 24 compliant
- · Five-year warranty
- 120-277 Vac











General Specifications

IntelliDAPT® Technology Auto reset from test setting

Self-adjusting timer

Self-adjusting ultrasonic thresholds Automatic false-on/false-off corrections

LED lamp Green—ultrasonic motion

Timer timeout Automatic mode: 8–30 min. (self-adjusts based on occupancy)

Test mode: 8 seconds (for an easy check at installation)

Ultrasonic (US) output OMNIUS500: 40kHz output

OMNIUS1000 and OMNIUS2000: 32kHz output

Coverage 500–2,000 square feet (depending on model)

Power requirements 120-277VAC; 50/60Hz

Single phase only

Output 24 VDC active high-logic control signal with short circuit protection

Relay Contact Rating 20A: 120VAC Incandescent

20A: 120 or 277VAC Magnetic Ballast 16A: 120 or 277VAC Electronic Ballast

1HP: 120VAC Motor Load 3/4HP: 277VAC Motor Load

Operating environment Indoor use only

Operating temperature: 32° to 104°F (0° to 40°C) Relative humidity (non-condensing): 0% to 95%

Construction Casing - rugged, high-impact, injection-molded plastic KJB ABS

Cycolac (UL-945VA) flame class rating, UV inhibitors

Color-coded leads are 6" long

Size and weight Size: 4.5" diameter, 3.4" height (114 mm diameter, 86.4mm height)

Weight: 8.2 oz (232g)


Color Off-white


Mounting using a3 inch mud ring attached to 4 inch square electrical box

Recommended MAX mounting height: 12ft.

Certifications UL and cUL listed
Warranty Five years

Ordering Information





Ceiling Sensor 2000 Sq Ft coverage

