



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



OP10 HMI

The TECO OP10 monochrome HMI offers a simple but powerful user interface for the SG2 (Ver 3) programmable Logic Relay. Monitor data registers in real time, change parameters, perform switching functions, list alarms, and transfer data between networked SG2's*.

- 192 x 64 pixel display
- 24-key keypad
- Two serial ports:
 - COM1 supports programming and point-to-point communications
 - RS485 supports multi-drop networks
- Supports Modbus RTU
- Password protection
- Import bitmaps
- Offline program simulation
- Bar graphs, trend charts, alarm logging



FREE Programming Software

Program the OP10 using simple fill-in-the-blank object windows. Establish network links to remote devices. Create dynamic text, trend charts, bargraphs, alarm logs, and more. View and verify your program in simulation mode. Download software free at: www.bb-elec.com/bb-elec/software/PLC/OP10-PCLINKV2.1setup.exe

Dynamic Text




Trending



Bar Graphs



Simulation




Simple Setup

Part Number	Description	Price
OP10	4.3" Monochrome Graphic Panel, 192 x 64 pixels, 4 Function Keys, Numeric Keypad, 2 serial ports, 24VDC input power	
OP10-PL01	Cable (9-pin Serial, PC to 9-pin Serial, OP10)	
SG2-PL01	SG2 to OP10 Communication Cable	
SG2-Software	SG2 & OP10 Programming S/W. Available on CD or FREE via download.	

General Specifications	
Power	DC24V, -15% ~ +10%
Current Consumption	80mA Max
Approvals	UL, CE
Communication Interface	COM1: (9-pin, D-SUB, female) RS-232/422; RS485: terminal screws
Environmental Rating	IP65 (front of panel)
Maximum Devices	8 without repeater; 255 with repeater
Dimensions	179.5 x 101.5 x 33mm (7.07 x 4.00 x 1.30")
Weight	460g (~1 lb)
Environmental	
Operating Temperature	0°C ~ 55°C (32°F ~ 131°F)
Storage Temperature	-40°C ~ 70°C (-40°F ~ 158°F)
Relative Humidity	10% ~ 95%, non-condensing
Vibration	1.75mm displacement, 5 - 9Hz
Impact	15G, 11ms, vertical from X, Y, Z directions

Dimensions



Communication with one SG2 via programming port



Multi-drop Modbus communications over RS485 network



*SG2 must be V-series to communicate on RS485.