



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




# Fiber Optic Receiver

OPF2412, OPF2412T



## Features:

- Up to 5Mbps operation
- 850nm wavelength
- ST<sup>®</sup> style port
- CMOS and TTL compatible
- Wave solderable
- Wide temperature range





## Description:

The OPF2412 family is a low cost digital output fiber optic receiver. The lensed optical system keeps the receiver response consistent for all fiber sizes which makes it ideal for use on fibers as small as 50/125 $\mu$ m. The design incorporates a monolithic photo-IC comprised of a photodetector and DC amplifier driving an open collector output Schottky transistor. The output makes the OPF2412 compatible with TTL and CMOS logic. The receiver is designed to operate from a single +5 V supply. A bypass capacitor (0.1 $\mu$ F ceramic) should be connected from V<sub>CC</sub> to GND of the receiver.

## Applications:

- Industrial Ethernet equipment
- Copper-to-fiber media conversion
- Intra-system fiber optic links
- Video surveillance systems



"T" suffix = Threaded ST<sup>®</sup> package

PIN	FUNCTION
1	Not Connected
2	V <sub>CC</sub>
3	GND
4	Not Connected
5	Not Connected
6	V <sub>OUT</sub>
7	GND
8	Not Connected



RoHS



ESD Class 2

ST<sup>®</sup> is a registered trademark of AT&T.

Pins 3 & 7 are electrically connected to the header.  
Pins 1,4,5 & 8 are mechanically connected together.

## General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.



OPTEK Technology, Inc.  
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
www.optekinc.com | www.ttelectronics.com

# Fiber Optic Receiver

OPF2412, OPF2412T



## Mechanical Data





OPF2412

PINS 1, 4, 5, & 8 - .020 X .015  
[0.51 X 0.38]

PINS 2, 3, 6, & 7 -  $\varnothing$ .018  
[0.46]

OPF2412T



PINS 1, 4, 5, & 8 - .020 X .015  
[0.51 X 0.38]

PINS 2, 3, 6, & 7 -  $\varnothing$ .018  
[0.46]

DIMENSIONS ARE IN: [MILLIMETERS]  
INCHES

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

OPTEK Technology, Inc.  
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
www.optekinc.com | www.ttelectronics.com

### Electrical Specifications


Absolute Maximum Ratings ( $T_A = 25^\circ \text{C}$ unless otherwise noted)	
Storage Temperature Range	$-55^\circ \text{C}$ to $+85^\circ \text{C}$
Operating Temperature Range	$-40^\circ \text{C}$ to $+85^\circ \text{C}$
Lead Soldering Temperature <sup>(1)</sup>	$260^\circ \text{C}$
Supply Voltage	$-0.5 \text{ V}$ to $7.0 \text{ V}$
Output Current	$25 \text{ mA}$
Output Voltage	$-0.5 \text{ V}$ to $18.0 \text{ V}$
Open Collector Power Dissipation	$40 \text{ mW}$
Fan Out (TTL)	$5^{(2)}$

Electrical Characteristics ( $T_A = 25^\circ \text{C}$ unless otherwise noted)						
SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
$I_{OH}$	High Level Output Current		5	250	$\mu\text{A}$	$V_O = 18 \text{ V}$ , $P_R < -40 \text{ dBm}$
$V_{OL}$	Low Level Output Voltage		0.4	0.5	$\text{V}$	$I_O = 8 \text{ mA}$ , $P_R > -24 \text{ dBm}$
$I_{CCH}$	High Level Supply Current		3.5	6.3	$\text{mA}$	$V_{CC} = 5.25 \text{ V}$ , $P_R < -40 \text{ dBm}$
$I_{CCL}$	Low Level Supply Current		6.2	10	$\text{mA}$	$V_{CC} = 5.25 \text{ V}$ , $P_R > -24 \text{ dBm}$
$P_{RH}$	Peak Input Power Level, Logic HIGH			0.1	$\mu\text{W}$	$\lambda_p = 850 \text{ nm}$
$P_{RL}$	Peak Input Power Level, Logic LOW	2.9		120	$\mu\text{W}$	$\lambda_p = 850 \text{ nm}$ , $I_{OL} = 8 \text{ mA}$
$P_{RL}$	Peak Input Power Level, Logic LOW	4.0		100	$\mu\text{W}$	$-40^\circ \text{C} \leq T_A \leq +85^\circ \text{C}$
$t_{PLHR}$	Propagation Delay LOW to HIGH		65		$\text{ns}$	$P_R = -21 \text{ dBm}$ , Data Rate = $5 \text{ MBd}$
$t_{PHLR}$	Propagation Delay HIGH to LOW		49		$\text{ns}$	$P_R = -21 \text{ dBm}$ , Data Rate = $5 \text{ MBd}$

#### Notes:

- Maximum of 5 seconds with soldering iron. Duration can be extended to 10 seconds when flow soldering. RMA flux is recommended.
- $8 \text{ mA}$  load ( $5 \times 1.6 \text{ mA}$ ),  $R_L = 560 \Omega$ .

Application Circuit



#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

OPTEK Technology, Inc.  
1645 Wallace Drive, Carrollton, TX 75006  
Ph: +1 972 323 2200  
www.optekinc.com | www.ttelectronics.com