



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us




Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

1	2	3	4	5	6	7
SIGN	DATE	DESCRIPTION			APPROVER	

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!



N=Number of contacts



P.C.B LAYOUT

THESE DRAWINGS AND SPECIFICATIONS  
ARE THE PROPERTY OF ON-SHORE  
TECHNOLOGY, INC. AND SHALL NOT BE  
REPRODUCED, COPIED OR USED IN ANY  
MANNER WITHOUT THE PRIOR WRITTEN  
CONSENT OF ON-SHORE TECHNOLOGY,  
INC.

#### Material

- Terminal body (Contact pin): Brass
- Wire guard: Stainless steel
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

#### Electrical

- Voltage rating: 250VAC
- Current rating: 8A
- Wire range:
  - Solid wire(AWG): 12-28
  - Stranded wire(AWG): 12-28
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.5KV
- Operating temperature: -30°C to +105°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety approval:

RoHS Compliant

PART NUMBER:

OSTHMXX7080

No. of Poles

02: 2 Poles

⋮

24: 24 Poles

COLOR

0: Black

5: Green

6: Blue

8: Grey (Standard)



TITLE		OSTHM 5.0mm Series Dip solder			DWG NO.	CUST NO.	Tolerance
PART NO.	OSTHMXX7080	APPROVED	CHECKED	DESIGNED			
Shi jun 2006.11.01	Marvin 2006.06.26	Marvin 2006.06.26	Marvin 2006.06.26				
					UNIT: mm	SCALE: NONE	X. ±0.50 X.X ±0.30 X.XX ±0.10 X* ±1°
							SHEET: 01/01 REV.: D

1	2	3	4	5	6	7
---	---	---	---	---	---	---