

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



1	2	3	4	5	6	7
SIGN	DATE	DESCRIPTION			APPROVER	

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!



N=Number of poles

P.C.B LAYOUT



THESE DRAWINGS AND SPECIFICATIONS
ARE THE PROPERTY OF ON-SHORE
TECHNOLOGY, INC. AND SHALL NOT BE
REPRODUCED, COPIED OR USED IN ANY
MANNER WITHOUT THE PRIOR WRITTEN
CONSENT OF ON-SHORE TECHNOLOGY,
INC.

Material

- Terminal body
- (metal housing): Brass(CuZn)
- Terminal screw: Steel Zinc plating “-” slot type
- Contacts: Brass
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC / 300VAC
- Current rating: 16A / 17.5A
- Wire range: 0.5-1.5mm²
Solid wire(AWG): 12-28
Stranded wire(AWG): 12-28
- Torque: 3.5lb-in / 0.4N.m
- Screw: M3
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV / 2.5KV
- Operating temperature: -30°C to +105°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: cULus FI

RoHS Compliant

PART NUMBER:

OSTVIXX4151

No. of Poles
02: 2 Poles
03: 3 Poles
...
24: 24 Poles

COLOR:
0: Black
5: Green (Standard)
6: Blue
8: Grey



TITLE		OSTVI 7.5 SERIES 180° wire inlet (with cover)			DWG NO.		OSTVIXX4151.DWG	Tolerance
PART NO.	OSTVIXX4151							
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.				
Shi Jun 2006.10.20	Marvin 2006.10.20	Marvin 2006.10.20	Marvin 2006.10.20		Ø1.60	UNIT: mm	X. ±0.50	X. X. ±0.30
						SCALE: NONE	X.XX ±0.10	X* ±1°
						SHEET: 01/01		
						REV.: E		