



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Heavy-Duty C13 to C14 PDU-Style Power Extension Cable - 15A, 100–250V, 14 AWG, 3 ft., Green

MODEL NUMBER: P005-003-AGN



Computer power extension cord connects devices with C13/C14 power connectors or extends your existing power connection by 3 ft.

### Features

#### C14-to-C13 Power Cable for Network Devices That Require a Heavy-Gauge Connection

This IEC-320-C14 to IEC-320-C13 cable features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This C14 male to C13 female cord can be used to connect a computer, server, monitor or drive to a UPS system or PDU or replace or upgrade the standard power cord provided by the device's manufacturer. The three-foot length helps reduce cable clutter and minimize the risk of tripping.

#### Color-Coded to Avoid Misidentification That Can Cause Costly Downtime

This computer power extension cord features a green SJT jacket and fully molded green ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

### Highlights

- Recommended for powering computers, servers and other network devices
- 3 ft. length allows flexibility in placing devices, while avoiding cable clutter
- PDU-style cord replaces or upgrades standard power cord provided by manufacturer
- Color-coded green for fast, easy identification in a crowded rack or workstation
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

### Applications

- Connect devices like computers, servers and monitors to a PDU up to 3 ft. away in your data center
- Extend an existing power connection up to 3 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

### Package Includes

- P005-003-AGN Heavy-Duty C13 to C14 PDU-Style Power Extension Cable, 3 ft., Green

## Specifications



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                     |                               |
|-------------------------------------|-------------------------------|
| UPC Code                            | 037332198983                  |
| Country/Region                      | North America                 |
| Power Cord Application              | PC; Monitor; Server; PDU; UPS |
| <b>INPUT</b>                        |                               |
| Maximum Input Amps                  | 15                            |
| Cable Length (ft.)                  | 3                             |
| Cable Length (m)                    | 0.9                           |
| Cable Length (in.)                  | 36                            |
| Voltage Compatibility (VAC)         | 250                           |
| Cable Length (cm)                   | 91.44                         |
| <b>PHYSICAL</b>                     |                               |
| Power Cord Jacket Type              | SJT                           |
| Wire Gauge (AWG)                    | 14                            |
| Wire Gauge (OD - mm <sup>2</sup> )  | 2.08                          |
| Shipping Dimensions (hwd / in.)     | 9.90 x 7.00 x 0.50            |
| Shipping Dimensions (hwd / cm)      | 25.15 x 17.78 x 1.27          |
| Shipping Weight (lbs.)              | 0.44                          |
| Shipping Weight (kg)                | 0.20                          |
| Color                               | Green                         |
| Number of Conductors                | 3                             |
| <b>ENVIRONMENTAL</b>                |                               |
| Operating Temperature Range         | -4 F TO 140 F (-20 C TO 60 C) |
| Storage Temperature Range           | -4 F TO 140 F (-20 C TO 60 C) |
| Operating Humidity Range            | 10-85% RH                     |
| Storage Humidity Range              | 10-85% RH                     |
| <b>CONNECTIONS</b>                  |                               |
| Side A - Connector 1                | IEC-320-C14                   |
| Side B - Connector 1                | IEC-320-C13                   |
| <b>WARRANTY</b>                     |                               |
| Product Warranty Period (Worldwide) | Lifetime limited warranty     |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>