

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









IEC C14 to IEC C15 Power Cable - Heavy Duty, 15A, 100-250V, 14 AWG, 2 ft., Orange

MODEL NUMBER: P018-002-AOR











Heavy-duty C14 to C15 power cord connects a PoE network switch or other device with a C16 power inlet to a PDU or UPS system.

Features

C15 to C14 Power Cord for Network Devices That Require a Heavy-Gauge Connection

This 250V C15 to C14 cable features 14 AWG wire suitable for high power connections, making it reliable for large server applications that require a higher-rated, heavier-gauge cable. The C15 connector is designed for higher-temperature devices, such as electric kettles, PoE (Power over Ethernet) switches with high-wattage power supplies, and similar network components. This IEC C14 to IEC C15 cord can also replace or upgrade the standard power cord provided by the device's manufacturer. The two-foot length helps reduce cable clutter and minimize the risk of tripping.

Color-Coded to Avoid Misidentification That Can Cause Costly Downtime

This C15 to C14 power cable features an orange SJT jacket and fully molded orange ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

Highlights

- Recommended for powering PoE switches with high-wattage power supplies
- 2 ft. length allows flexibility in placing devices, while avoiding cable clutter
- C14 to C15 power cable replaces or upgrades original manufacturer's power cord
- Color-coded orange for fast, easy identification in a crowded rack or workstation
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like highwattage PoE switches to a PDU up to 2 ft. away in your data center
- Update or replace the standard power cord provided by a device's original manufacturer
- Extend an existing power connection by 2 ft.

Package Includes

P018-002-AOR IEC C14 to IEC
C15 Power Cable, 2 ft., Orange

Specifications

OVERVIEW	
UPC Code	037332199102
Country/Region	North America
Power Cord Application	PC; Monitor; Server; PDU; UPS



INPUT		
Maximum Input Amps	15	
Cable Length (ft.)	2	
Cable Length (m)	0.6	
Cable Length (in.)	24	
Voltage Compatibility (VAC)	250	
Cable Length (cm)	60.96	
PHYSICAL		
Power Cord Jacket Type	SJT	
Wire Gauge (AWG)	14	
Wire Gauge (OD - mm²)	2.08	
Shipping Dimensions (hwd / in.)	9.90 x 7.00 x 0.50	
Shipping Dimensions (hwd / cm)	25.15 x 17.78 x 1.27	
Shipping Weight (lbs.)	0.33	
Shipping Weight (kg)	0.15	
Color	Orange	
Number of Conductors	3	
ENVIRONMENTAL		
Operating Temperature Range	-4 F to 221 F (-20 TO 105 C)	
Storage Temperature Range	-4 F to 221 F (-20 TO 105 C)	
Operating Humidity Range	10-85% RH	
Storage Humidity Range	10-85% RH	
CONNECTIONS		
Side A - Connector 1	IEC-320-C14	
Side B - Connector 1	IEG-320-C15	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies