

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









www.tripplite.com



# IEC C14 to IEC C15 Power Cable - Heavy Duty, 15A, 250V, 14 AWG, 3 ft., Blue

# MODEL NUMBER: P018-003-ABL











Connects a PDU or UPS system with a C14 input port to network hardware, such as computers, servers and storage drives, with C15 power connectors.

#### Description

The P018-003-ABL Heavy-Duty Computer Power Cord features a blue SJT jacket and fully molded blue ends, allowing you to easily identify your connections in a crowded rack or workstation. It features a C14 male connector on one end and a C15 female connector on the other for attaching a high-voltage computer, server or storage drive to a PDU or UPS system.

This three-foot 15A cord supports voltages up to 250V. It's UL-listed and features a flexible SJT jacket and 14 AWG wire for easy routing through tight areas. The P018-003-ABL is recommended for Cisco, HP and other hardware that use C15 power connectors.

#### **Features**

### Safe, Reliable Power Solution

- Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- · Ideal for replacing an old or lost cord
- Recommended for Cisco, HP and other C15-compatible hardware

#### Color-Coded Cable and Connectors

• Colored blue for easy identification in crowded rack or workstation

#### **Optimum Construction**

- 14 AWG wire
- Flexible SJT jacket
- 250V/15A rating

## **Highlights**

- Easy-to-identify blue SJT jacket and fully molded blue ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

## Package Includes

P018-003-ABL Heavy-Duty
 Computer Power Cord, Blue, 3
 ft.



• UL-listed

# **Specifications**

| OVERVIEW                        |                               |
|---------------------------------|-------------------------------|
| UPC Code                        | 037332198518                  |
| Country/Region                  | North America                 |
| Power Cord Application          | PC; Monitor; Server; PDU; UPS |
| INPUT                           |                               |
| Maximum Input Amps              | 15                            |
| Cable Length (ft.)              | 3                             |
| Cable Length (m)                | 0.9                           |
| Cable Length (in.)              | 36                            |
| Voltage Compatibility (VAC)     | 250                           |
| Cable Length (cm)               | 91.44                         |
| PHYSICAL                        |                               |
| Power Cord Jacket Type          | SJT                           |
| Wire Gauge (AWG)                | 14                            |
| Wire Gauge (OD - mm²)           | 2.08                          |
| Shipping Dimensions (hwd / in.) | 9.900 x 7.000 x 0.500         |
| Shipping Dimensions (hwd / cm)  | 25.15 x 17.78 x 1.27          |
| Shipping Weight (lbs.)          | 0.4400                        |
| Shipping Weight (kg)            | 0.20                          |
| Color                           | Blue                          |
| Number of Conductors            | 3                             |
| ENVIRONMENTAL                   |                               |
| Operating Temperature Range     | -4 F to 221 F (-20 TO 105 C)  |
| Storage Temperature Range       | -4 F to 221 F (-20 TO 105 C)  |
| Operating Humidity Range        | 10-85% RH                     |
| Storage Humidity Range          | 10-85% RH                     |
| CONNECTIONS                     |                               |
| Side A - Connector 1            | IEC-320-C14                   |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| Side B - Connector 1                | IEC-320-C15               |
|-------------------------------------|---------------------------|
| WARRANTY                            |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>