

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Heavy-Duty Power Extension Cord, 20A, 12AWG (Left Angle IEC-320-C19 to IEC-320-C20), 2-ft.

MODEL NUMBER: P036-002-19LA



Highlights

- C19 Left Angle to C20 Power Cord, 2 ft.
- 12AWG (3.31mm²) x 3C, 20 Amp
 Rated, 100-250V
- RoHS Approved

Package Includes C19 Left Angle to C20 Power Cable, 2 ft.

Description

Use Tripp Lite's P036-002-19LA in server applications that require a higher rated, heavier gauge cable. C19 Left Angle to C20 connectors, 3 x 12ga (3.31mm²) conductors, 20AMP rated, 100-250V - ideal for use with Blade Server Chassis.

Features

- Molded, Heavy-Duty Power Cord, 2 ft.
- IEC-60320-C19 Left Angle to IEC-60320-C20
- 12AWG (3.31mm²) x 3C, SJTW, 20A, 100-250Volt
- RoHS Approved

Specifications

OVERVIEW		
UPC Code	037332156501	
INPUT		
Cable Length (ft.)	2	
Cable Length (m)	0.6	
PHYSICAL		
Power Cord Jacket Type	SJTW	
Wire Gauge (AWG)	12	





Wire Gauge (OD - mm²)	3.31mm ²	
Shipping Dimensions (hwd / in.)	6.000 x 7.800 x 9.400	
Shipping Dimensions (hwd / cm)	15.24 x 19.81 x 23.88	
Shipping Weight (lbs.)	5.2000	
Shipping Weight (kg)	2.36	
Color	Black	
CONNECTIONS		
Side A - Connector 1	IEC-320-C20	
Side B - Connector 1	IEC-320-C19 - LEFT ANGLE	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies