



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



L5-30P to L5-30R Heavy-Duty Extension Cord - 30A, 125V, 10 AWG, 15 ft., Black, Locking Connectors

MODEL NUMBER: P046-015-LL-30A



Heavy-duty extension cord connects your computer or other device with a NEMA L5-30P plug to a NEMA L5-30R outlet.

Features

Heavy-Duty Extension Cable for Network Devices That Require a Heavy-Gauge Connection

This cord features 10 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. It can be used to connect a computer, server or other device with a NEMA L5-30P plug to a wall outlet, PDU or UPS system with a NEMA L5-30R outlet. The 15-foot length allows you great flexibility in placing equipment with respect to the power outlet.

Locking Connectors Help Prevent Accidental Disconnection and Expensive Downtime

Having a cable come loose accidentally can mean the loss of power and costly downtime. Locking connectors on each end help you avoid such danger, protecting critical equipment by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the power cord always stays connected.

Highlights

- Recommended for powering computers, servers and other network devices
- 15 ft. length allows great flexibility in placing devices in relationship to AC outlet
- Heavy-duty cord replaces or upgrades standard power cord provided by manufacturer
- Thick 10 AWG wire gauge manages high power levels required for larger equipment
- Locking connectors maintain secure link to avoid loss of power and costly downtime

Applications

- Connect devices like computers, servers and monitors to a PDU in your data center
- Extend an existing power connection up to 15 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

- P046-015-LL-30A L5-30P to L5-30R Heavy-Duty Extension Cord, 15 ft., Black, Locking Connectors

Specifications

OVERVIEW



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|----------------------------|
| UPC Code | 037332200952 |
| Country/Region | North America |
| Power Cord Application | PDU; UPS |
| INPUT | |
| Maximum Input Amps | 30 |
| Cable Length (ft.) | 15 |
| Cable Length (m) | 4.6 |
| Cable Length (in.) | 180 |
| Voltage Compatibility (VAC) | 125 |
| Cable Length (cm) | 457.20 |
| PHYSICAL | |
| Power Cord Jacket Type | SJT |
| Wire Gauge (AWG) | 10 |
| Wire Gauge (OD - mm ²) | 5.26 |
| Shipping Dimensions (hwd / in.) | 0.50 x 10.30 x 14.70 |
| Shipping Dimensions (hwd / cm) | 1.27 x 26.16 x 37.34 |
| Shipping Weight (lbs.) | 4.00 |
| Shipping Weight (kg) | 1.81 |
| Color | Black |
| Number of Conductors | 3 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 41 F TO 95 F (5 C TO 35 C) |
| Storage Temperature Range | 41 F TO 95 F (5 C TO 35 C) |
| Operating Humidity Range | 0-65% RH |
| Storage Humidity Range | 0-65% RH |
| CONNECTIONS | |
| Side A - Connector 1 | NEMA L5-30P |
| Side B - Connector 1 | NEMA L5-30R |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>