

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# IEC 309 to C19, Heavy-Duty Extension Cord - 16A, 250V, 16 AWG, 10 ft., Black

MODEL NUMBER: P070-010



IEC 309 (2P+G) to C19 extension cord connects a high-output device with a C20 power inlet to an IEC 309 connector on a PDU.

#### **Features**

Heavy-Duty Extension Cable for Network Devices That Require a Heavy-Gauge Connection
This heavy-duty extension cord features 16 AWG wire suitable for high power connections, making it a
reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This cord
can be used to connect a server, router, network switch or blade server enclosure to a PDU or replace or
upgrade the standard power cord provided by the device's manufacturer. The 10-foot length allows you
great flexibility in placing equipment with respect to the power outlet.

#### **Highlights**

- Recommended for powering servers, routers and other highoutput network devices
- 10 ft. length allows great flexibility in placing devices in relationship to AC outlet
- Heavy-duty extension cord replaces or upgrades standard manufacturer power cord
- 16 AWG wire gauge manages high power levels required for larger equipment

#### **Applications**

- Connect high-output devices like servers and routers to a PDU up to 10 ft. away in your data center
- Extend an existing power connection up to 10 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

#### **Package Includes**

P070-010 IEC 309 to C19,
 Heavy-Duty Extension Cord, 10
 ft., Black

### **Specifications**

OVERVIEW	
UPC Code	037332160706
Country/Region	North America
Power Cord Application	Server; PDU





INPUT		
Maximum Input Amps	16	
Cable Length (ft.)	10	
Cable Length (m)	3.1	
Voltage Compatibility (VAC)	250	
PHYSICAL		
Power Cord Jacket Type	SJT	
Wire Gauge (AWG)	16	
Wire Gauge (OD - mm²)	1.29	
Shipping Dimensions (hwd / in.)	12.80 x 8.90 x 0.50	
Shipping Dimensions (hwd / cm)	32.51 x 22.61 x 1.27	
Shipping Weight (lbs.)	1.20	
Shipping Weight (kg)	0.54	
Color	Black	
Number of Conductors	3	
CONNECTIONS		
Side A - Connector 1	IEC-320-C19	
Side B - Connector 1	IEC-309 16A 2P+E	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>