imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



2 THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. DIMENSIONS in. STUD PANDUIT A ±.02 H ±.01 PART NUMBER SIZE ±.01 ±.02 ±.02 W -С W М .78 .31 .35 .62 .15 #6 P10-6RHT6 19.81) (7.87) (8.89) (15.75) (3.81)

.17

.20

.27

А

Μ

LISTED

587H E52164 H DIA

C RAD

BRAZED

SEAM

SERRATED

BARREL

BEVELED

EDGE

.13 ±.01 (3.30)

DIA

.22 ±.01 (5.59)

DIA

B

В

NOTES:

P10-8RHT6

P10-10RHT6

P10-14RHT6

1. RECOMMENDED FOR: A. #12-10 AWG SOLID OR STRANDED COPPER WIRE * B. 650° F (343° C) MAX. TEMP RATING

#8

#10

1/4"

- 2. MATERIAL: A. STAMPING - .04" [1.02] THK COPPER, NICKEL PLATED
- 3. PACKAGE QTY: STD. PKG. L = 50 BULK PKG. - D = 500
- 4. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS
- 5. INSTALLATION TOOL: CT-100, CT-200, A. PANDUIT APPROVED: CT-160, CT-260, CT-570 CT-1570

.78

.81

.96

19.81)

20.57) (9.65)

.31

(7.87)

.38

.53

.35

.33

.42

24.38)(13.46)(10.67)(17.78)(6.86)

.62

(8.89) (15.75) (4.32)

.62

(8.38) (15.75) (5.08)

.70

* APPROVED FOR USE WITH # 14 - 10 AWG SOLID OR STRANDED COPPER WIRE WHEN INSTALLED WITH THE CT-570 OR CT-1570 TOOLS

A								#12-10 BARREL NON INSULATED RING TONGUE, HIGH TEMPERATURE, 650° F CUSTOMER DRAWING
								ITEM REVISION NAME N41267BA/02 DATASET FILE NAME N41267BA/02
								UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .X ± .xxx ± . .Xx ±
DA/16	02	1/15	JHNU	TMR	RGB	ADDED CULUS LOGO REVISED TITLE BLOCK	N41267BA-DC	THIRD ANGLE PROJECTION A41267
D10100	REV	DATE	BY	СНК	APR	DESCRIPTION 2	ECN	EJD CHK SCALE N/A SHT 1 OF 1

Т