imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART #	WIRE	SIZE	DIMENSIONS in. [mm]						
	AWG	mm²	L ± .03 [0,8]	B± .01 [0,3]	C ± .015 [0,4]	D± .01 [0,3]	E ± .01 [0,3]		
P18-P47*	#22-18	0,5–1,0	.75 [19,1]	.07 [1,8]	.49 [12,4]	.14 [3,6]	.06 [1,5]		
P14-P47*	#16-14	1,5–2,5	.75 [19,1]	.07 [1,8]	.49 [12,4]	.16 [4,1]	.08 [2,0]		
P10-P55	#12-10	4,0-6,0	.79 [20,1]	.11 [2,8]	.55 [14,0]	.22 [5,6]	.15 [3,8]		



В


NOTES:

В

 USED FOR: A.SOLID OR STRANDED COPPER WIRE B. 302°F [150°C] MAX. OPERATING TEMPERATURE
INSTALLATION TOOLS:

2

- A. PANDUIT APPROVED: CT-100A, CT-160, CT-200, CT-260, CT-1570, CT-600-A (CT-570CH), CT-2500 (CT-2570CH)
- 3. WIRE STRIP LENGTH: 9/32" +1/32 [7,1+0,8]
- 4. MATERIAL:
- A. STAMPING: .03" [0,8] THK COPPER, TIN PLATED 5. SEE www.panduit.com FOR PACKAGE QUANTITIES INDICATED BY PART NUMBER SUFFIX
- 6. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT



FI[®] E52164

								TITLE					
A [PIN TERMINAL, NON-INSULATED,					
								CUSTOMER DRAWIN				WING	
ł								TTEM REVISION NAME N41334BA/06 DATASET FILE NAME N41334BA_DC/06A UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]					
											PANDUIT		
											MATERIAL:		
									.1 [2.54] .01 [.25]			SEE NOTES	
0A/12	06	09.19.12	JBN	LCA	VMB	ADDED METRIC EQUIVALENT. REVISED NOTES. UPDATED TO CURRENT STANDARDS.	A41334			TH I PR	IRD ANGLE OJECTION	A41334	
D10100E	06 Rev	DATE	BY	СНК	APR	DESCRIPTION	ECN	DRAWN BY	DATE _	снк RLS	SCALE N.T.S.	SHEET 1 OF 1	A
_	2									1			