

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

4K HDMI Audio Extractor with TOSLINK, RCA and 3.5 mm Stereo Output, 7.1 Channel, HDCP 2.2, 4K x 2K @ 60 Hz

MODEL NUMBER: P130-000-AUD4K6











Separates the audio track from an HDMI audio/video signal and sends it to a stereo receiver, speakers or other separate audio system. Ideal for connecting a Blu-ray player or other HDMI source to speakers with no HDMI input.

Description

The P130-000-AUD4K6 4K HDMI Audio Extractor connects an HDMI source, such as a Blu-ray player or desktop computer, to audio speakers that don't have an HDMI input port. Recommended for home or office workstations, digital signage, and classrooms, it can save you money by eliminating the need to upgrade to a new audio system or speakers.

The P130-000-AUD4K6 extracts the audio track from the HDMI signal and sends it directly to an alternate digital or analog non-HDMI audio device. To power the unit, connect the included USB Micro-B cable between the P130-000-AUD4K6 and a USB port on the HDMI source or a USB charger.

The compact HDMI audio de-embedder/extractor unit features 3.5 mm stereo, TOSLINK digital optical and RCA digital audio outputs to match most non-HDMI receivers and audio devices. It supports two-channel stereo and multi-channel audio up to 7.1 surround sound. It also supports uncompressed audio, such as LPCM, and compressed audio formats, including DTS and Dolby Digital. LEDs indicate when the unit is receiving power and transmitting an audio/video signal.

On the video side, the P130-000-AUD4K6 transmits UHD video resolutions up to $3840 \times 2160 \text{ (4K} \times 2K)$ at 60 Hz. It supports 24-bit True Color (8 bits per channel) at 4K x 2K, 36-bit Deep Color (12 bits per channel) at 1080p and optional 3D formats up to 60 Hz. It complies with HDMI 2.0 and HDCP 2.2 specifications to conform to the latest equipment and encryption standards.

Features

Highlights

- Features 3.5 mm stereo,
 TOSLINK optical and RCA audio outputs
- Supports multi-channel audio up to 7.1 surround sound
- Supports uncompressed audio, such as LPCM
- Supports compressed audio, such as DTS and Dolby Digital
- Transmits video resolutions up to 3840 x 2160 (4K x 2K) @ 60
 Hz

System Requirements

- Source device with HDMI output
- Audio device with 3.5 mm,
 TOSLINK or RCA audio input

Package Includes

- P130-000-AUD4K6 4K HDMI
 Audio Extractor
- USB Micro-B cable, 3 ft.
- Owner's manual



Extracts Audio from an HDMI Signal and Sends It to a Separate Audio Device

- Recommended for connecting an HDMI source to speakers that don't have HDMI input
- Ideal for home or office workstations, digital signage or classroom use
- 3.5 mm stereo, TOSLINK and RCA audio outputs connect to analog or digital non-HDMI audio equipment (audio and HDMI cables sold separately)
- LEDs indicate the unit is receiving power or transmitting an audio/video signal

Versatile Audio Options

- Supports 2-channel stereo and multi-channel audio up to 7.1 surround sound
- Supports uncompressed audio, such as LPCM
- Supports compressed audio, such as DTS and Dolby Digital

Vibrant UHD Video

- Transmits UHD video resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Supports 24-bit True Color (8 bits per channel) at 4K x 2K
- Supports 36-bit Deep Color (12 bits per channel) at 1080p
- Supports optional 3D formats up to 60 MHz

Simple Plug-and-Play Operation

- No software or drivers required
- Included 3 ft. USB Micro-B cable connects to HDMI source or USB charger to power the unit
- Complies with HDMI 2.0 and HDCP 2.2 standards
- Compact unit measures just 3 x 2.4 x 1 in. for easy integration with your A/V setup

Specifications

OVERVIEW		
UPC Code	037332203434	
Technology	HDMI (All types); Stereo Audio; Toslink/SPDIF	
INPUT		
Cable Length (ft.)	0	
Cable Length (m)	0	
PHYSICAL		
Color	Black	
CONNECTIONS		
Side A - Connector 1	HDMI (FEMALE)	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Product Warranty Period (Worldwide)	2-year limited warranty	
WARRANTY		
Side B - Connector 4	RCA (FEMALE)	
Side B - Connector 3	3.5MM (FEMALE)	
Side B - Connector 2	TOSLINK (MALE)	
Side B - Connector 1	HDMI (FEMALE)	
Side A - Connector 2	MICRO-USB B (FEMALE)	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies