# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





### Linear Polarity RFID Panel Antenna PAV90209H





### 902-928 MHz 9 dBi LINEAR POLARITY PANEL

The Laird PAV90209H antenna is a linearly polarized panel antenna that provides reception and transmission of signals in the 902-928 MHz frequency band. Laird's industry-renowned design methodology achieves maximum efficiency and performance across the entire frequency band.

Both VSWR and efficiency are excellent and allow the user to achieve the maximum performance for an antenna of this type. The antenna is housed in a heavy duty radome enclosure that can be directly wall mounted. An optional articulating mount allows either wall or mast mounting. The antenna is offered with an integrated fixed connector with a variety of connector types or with coax cable.

### FEATURES **V**ROHS

- Low profile
- Extremely low VSWR and high efficiency
- Weather and UV resistant radome
- Wide range of connector options
- IP67 Enclosure

### **APPLICATIONS**

- Warehouse
- Distribution center
- Airports and hospitals
- Transit terminals
- Conveyer belt

Antenna Part Number Frequency Range Gain	PAV90209H 902 - 928 MHz 9 dBi 1.3:1
	9 dBi
Gain	
	1 3.1
Maxium VSWR	1.5.1
3 dB Beamwidth - Azimuth	70°
Front to Back Ratio	18 dB
Polarization	Linear
Maxium Input Power	10 Watts
Input Impedence	50 Ohms
Weight	2.3 lbs (1.04 Kg)
Mechanical Size	10.2" x 10.2" x 1.32"
Antenna Connection	Fixed, Type N Female / Coax Pigtail, N Male
Radome	High Strength PC
Mount Style	Threaded Stud
Temperature Operational	-40°C to +85°C
Temperature Storage	-40°C to +85°C
Ingress Protection	(Fixed N) IP67/(Pigtail) IP54
Lightning Protection	DC Grounded

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com


www.lairdtech.com



### Linear Polarity RFID Panel Antenna PAV90209H

### Smart Technology. Delivered.

### ANTENNA PATTERNS



#### **ORDERING GUIDE**

PART NO.	SPECIFICATIONS
PAV90209H-91NM	902-928 MHz panel, Linear, 9 dBi, 91 cm, N Male
PAV90209H-FNF	902-928 MHz panel, Linear, 9 dBi, Fixed, Type N Female

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

#### ANT-DS-PAV90209H 0515

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Termaduate Logo, and other marks are trade marks or registered trade marks of Laird no. an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.