

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








PowerStor PB Family

5.0 volt cylindrical supercapacitors



Description

Eaton PowerStor supercapacitors are unique, ultrahigh capacitance devices utilizing electrochemical double layer capacitor (EDLC) construction combined with new, high performance materials. This combination of advanced technologies allows Eaton to offer a wide variety of capacitor solutions tailored to specific applications that range from a few micro-amps for several days to several amps for milliseconds.

Features

- 5.0 volts
- · Low Equivalent Series Resistance (ESR)
- · High capacitance
- · Long cycle life
- · Low leakage currents
- · UL recognized

Applications

- · Bridge or hold-up power
- · Memory backup
- Battery swap out

General Specifications

Working voltage 5.0V Surge voltage 6.0V

Capacitance 0.1F to 1.0F

Capacitance tolerance -20% to +80% (20°C)

Operating temperature range -25°C to 70°C extended to 85°C

Powering Business Worldwide

The PowerStor brand of supercapacitors (formerly of the Bussmann Division of Cooper Industries) is now part of Eaton's Electrical Group, Electronics Division.



PowerStor is now part of Eaton Same great products plus even more.

Specifications

Nominal Capacitance (F)	Vertical Part Number	Horizontal Part Number	Maximum Initial ESR (Ω) (Equivalent Series Resistanc) Measured @ 100Hz	Nominal leakage current (μΑ) after 72 hours @ 20°C	Nominal dimensions (mm)	Typical mass (grams/piece)
0.1	PB-5R0V104-R	PB-5R0H104-R	4.0	3	5.5 x 10.8 x 12.5	1.1
0.47	PB-5R0V474-R	PB-5R0H474-R	1.0	7	8.5 x 16.8 x 14.0	2.4
1.0	PB-5R0V105-R	PB-5R0H105-R	0.5	12	8.5 x 16.8 x 21.5	3.5

Performance


Parameter	Capacitance change (% of initial value)	ESR (% of max. initial value)			
Life (1000 hours @ 70°C, 5.0Vdc or 85°C, 4.2Vdc)	≤ 30%	≤ 300%			
Storage - Low and High Temperature (1000 hours @ -25°C to +70°C)	≤ 30%	≤ 300%			

Dimensions (mm)


Vertical Part Number	Horizontal Part Number	Α	В	С	d'	D	D'	E	E'	F	Р
PB-5R0V104-R	PB-5R0H104-R	6.0	11.3	13.0	0.5	20	15	25	20	2.0	7.3
PB-5R0V474-R	PB-5R0H474-R	9.0	17.3	14.5	0.5	20	15	25	20	2.0	11.8
PB-5R0V105-R	PB-5R0H105-R	9.0	17.3	22.0	0.5	20	15	25	20	2.0	11.8
То	Maximum			± 0.02	Minimum			± 0.5			

Note: Longer lead is positive.

Vertical



Horizontal



Part numbering system

Р	В		5	R	0				 R
Family Code	Version	Voltage (V) R = Decimal				Configuration	Capacitance (µF)		Ontion
			Comiguration	Value	Multiplier	Option			
P Family	High capacitance		5R0 =	= 5.0V		V = Vertical H = Horizontal	Example: 474 = 47 x 104μF or 0.47F		RoHS Compliant

Packaging information

- Standard packaging: Bulk, 100 units per bag
- · Larger bulk packages available on request

Part marking

- Manufacturer
- Capacitance (F)
- Max operating voltage (V)
- Family code (or part number)
- Polarity

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton Electronics Division 1000 Eaton Boulevard Cleveland, OH 44122 United States www.eaton.com/elx

© 2015 Eaton All Rights Reserved Printed in USA Publication No. 4393- BU-SB111358 March 2015

