imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PANDUIT®


Panduct[®] Installation Tools

- Panduit[®] Panduct[®] Bench Mount Wiring Duct Cutting Tool and Duct Cutting Tool easily cut Panduct[®] Wiring Duct and Cover
- DNT-100 notches duct sidewalls to bottom scoreline for tees
 and corner junctions
- TNR installs or removes Panduit nylon rivets, NR1-C and NR1-M, quickly and easily
- DFCT easily removes duct fingers in tight spaces

	Part Number	Part Description	Std. Pkg. Qty				
	Duct Cutting Tools						
-	PBDCT	Panduit bench-mount duct cutting tool. Cuts slotted wiring ducts and wiring duct covers with up to 6" width and up to 5" height. Full 78.74" (2 meter) measuring scale. Includes safety guarding.	1				
	DCT	Hand-held duct cutting tool.	1				
	Replacemen	t Blade Kit (includes blade and nylon insert)					
H	DCT-BLD	Replacement blade kit with blade and nylon insert.	1				
M	Replacement Nylon Insert						
	DCT-RI	Replacement nylon insert.	5				
DFCT	Duct Finger Cutting Tool (For use with all wide slotted duct types)						
	DFCT	Hand-held duct finger cutting tool.	1				
2	Duct Notching Tool (For use with all wide slotted duct types)						
	DNT-100	Hand-held sidewall notching tool.	1				
9	Nylon Rivet Installation Tool						
TNR	TNR	Hand-held nylon rivet installation tool.	1				
-	Nylon Rivets						
	NR1-C	Nylon rivet for use with TNR rivet tool. Mean pull-off force PVC: 90 lbs. Type NE/Type NNC: 70 lbs. Mean shear force: PVC 139 lbs. Type NE/Type NNC: 126 lbs.	100				
	NR1-M	Nylon rivet for use with TNR rivet tool. Mean pull-off force PVC: 90 lbs. Type NE/Type NNC: 70 lbs. Mean shear force: PVC 139 lbs. Type NE/Type NNC: 126 lbs.	1000				

Always use approved safety goggles when using any tools.

Total Thickness of	of Panel and Duct	Panel Hole Dia. Needed		ANSI Standard	
In.	mm	In.	mm	Drill Bit	
.158 – .187	4.0 - 4.7	.187	4.7	#15	
.188 – .218	4.8 - 5.5	.193	4.9	#11	
.219 – .250	5.6 - 6.4	.203	5.2	#7	
.251 – .281	6.5 – 7.1	.213	5.4	#4	



A. System

B3. Stainless Steel Ties

C1. Wiring Duct C2. Surface Raceway

PBDCT

DCT


C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors



E4. Permanent

E5. Lockout/ Tagout & Safety Solutions

> F. Index

