mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PCE-5124

LGA775 Intel® CoreTM 2 Quad SHB with VGA/Dual GbE/6 COM Ports



Features


- Complies with PICMG 1.3
- Supports LGA 775 Intel[®] Core™2 Quad processors with FSB 1333 MHz
- Supports dual channel DDR2 667/800 SDRAM up to 8 GB
- One PCIe x16 and Four x1 to backplane
- Dual gigabit Ethernet via two PCIe x1 lanes
- Supports 6 COM ports
- 6 SATA2 ports supports S/W SATA Raid 0, 1, 10, 5

S	nor	ifi <i>c</i>	atio	nc
פ	pec		9110	I S

	CPU	Core 2 Quad	Core 2 Duo	Pentium Dual-Core	;	Celeron 400	Sequence
	Max. Speed	Q9650	E8600	E5400		440	
		(3.0 GHz)	(3.33 GHz)	(2.7 GHz)		(2 GHz)	
Processor System	L2 Cache	12 MB	6 MB	2 MB		512 KB	
	Chipset	Intel Q35 + ICH					
	BIOS	AMI 16 Mb SPI	Flash x 2				
	Front Side Bus	1333/1066/800					
PCIe One x16 & Four x1 to backplane							
505	PCI		MHz PCI Masters t				
	Technology		DR2 667/800 MHz	DIMMs			
<i>l</i> lemory	Max. Capacity	8 GB					
	Socket	240-pin DIMM					
	External Card	PCle x16 Graph					
Graphics	Chipset Integrated		Aedia Accelerator 3				
Indpinios	VRAM		1 MB system memo	ory			
	Video Output	15-pin D-sub C					
	Interface	10/100/1000 M					
Ethernet	Controller	LAN1: Intel 825					
		LAN2: Intel 825					
	Connector	RJ-45 with LED	Connector x 2				
SATA2	Max. Data Transfer Rate	300 MB/s					
	Channel		ort S/W RAID 0,1,				
IDE			es NOT supports E				
	USB 2.0		HB, 4 ports on the				
	Serial		RS-232/422/485	with pin headers			
/O Interface	Parallel	1 (EPP/ECP)					
	FDD	1					
	PS/2		d keyboard, and Y-	cable is included in the	package)		
Vatchdog Timer	Output	System reset					
5	Interval	Programmable,					
Aiscellaneous	Audio Output			e (requires an audio exte		P/N: PCA-AUDIO-	HDA1E)
	CPU			or Q6200; DDR2 800 N			
Power Requirement	Voltage	+12 V	+5 V		+5 VSB	-12 V	-5 V
	Current	6.78 A	4.06 A		0.43 A	0	0
		Operating			Non-Operating (Storage)		
Environment	Temperature		$0 \sim 60^{\circ}$ C (32 $\sim 140^{\circ}$ F) (operation humidity:		-40° C ~ 85° C and 60° C @ 95% RH		
	· ·	40° C @ 85% RH Non-Condensing) 338.58 mm (L) x 126.39 mm (W) (13.3" x 4.98")			Non-Condensing		
Physical	Dimensions	338.58 mm (L)	x 126.39 mm (W) (13.3" x 4.98")			

AD\ANTECH Slot SBC & Passive Backplanes

PCE-5124



Ordering Information

Part Number	Gigabit LAN	VGA
PCE-5124G2-00A1E	Dual	Yes
PCE-5124VG-00A1E	Single	Yes

100

Bracket View







PCE-5124G2-00A1E

Packing List

Part Number	Description	Quantity
1700340640	FDD cable	x 1
1700003194	Serial ATA HDD data cable	x 2
1703150102	Serial ATA HDD power cable	x 2
1701260305	Printer + COM cable	x 1
1700060202	Y-cable for PS/2 mouse & keyboard	x 1
1700008461	USB cable with 4 ports	x 1
9689000068	Jumper pack	x 1
2002721020	User Note for Full-Size CPU Card	x 1
2002775001	User Note for LGA775 CPU	x 1
2190000902	Warranty Card	x 1
2002512410	Startup manual	x 1
2062512401	Utility CD	x 1

Optional Accessories

Part Number	Description
PCA-AUDIO-HDA1E	Audio extension module
1750000332	CPU cooler for LGA775 Pentium 4 processor up to 3.8 GHz (115 W), for 2U or higher chassis
1701092300	Dual-COM port cable kit for COM 1-2 (Only for G2 Version)
1700008762	Dual-COM port cable kit for COM 3-4 and COM 5-6