



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Cable kit , Riser Cards & I/O modules

## PCM-10586-9562E


### Installation Wiring Kit for PCM-9562

| Part No.   | Cable Description | Quantity | PCM-9562 Connector     | Terminating Connector                            |
|------------|-------------------|----------|------------------------|--|
| 1700160160 | Audio cable       | 1        | CN4                    | Cable 16-Pin (2.0 mm) Audio 16 cm                |
| 1700002142 | Ethernet cable    | 2        | CN10, CN12             | Ethernet Cable IDC10P 2.0 mm/RJ45 15cm           |
| 1700260250 | LPT port cable    | 1        | CN15                   | Cable 25 cm 25P to 26P ASS'Y LPT Port 2.0 mm     |
| 1700019109 | COM 4/5 cable     | 1        | CN42                   | A Cable 2 x 5P-2.0/D-SUB(M) 9P+D-SUB(M) 9P 25 cm |
| 1703100260 | USB Port cable    | 4        | CN20, CN21, CN28, CN29 | Wire 10P 26 cm 2.0 mm For USB 2 PORT             |
| 1703060191 | PS2 KB/MS Cable   | 1        | CN25                   | Cable 6P-2.0 mm Housing/6P (PS/2)/6P (K/B) 19 cm |
| 1700008941 | SATA Cable        | 3        | CN32, CN33, CN34       | Cable 7P/7P SATA L=30cm Lock                     |
| 1700001296 | VGA cable         | 1        | CN8                    | VGA Cable D-SUB 3 x 5P(F)/2x 8P-2.0 15 cm        |
| 1700100250 | COM1/2/3          | 3        | CN39, CN40, CN41       | F Cable IDE#2 10P-2.0/D-SUB 9P(M) 25 cm          |
| 1703150102 | SATA Power Cable  | 3        | None                   | SATA Power cable L= 10 cm                        |
| 170304015K | AT power cable    | 1        | CN5                    | A Cable 2 x 2P-4.2/B4P-5.08 x 2 15 cm            |

### Ordering Information

|                 |                    |
|-----------------|--------------------|
| PCM-10586-9562E | PCM-9562 cable kit |
|-----------------|--------------------|

### PCI Riser Card



## PCM-110


### 1-Slot PCI Riser Card for 5.25" Biscuit SBCs

CE FCC

Fits in PCM-95XX series  
Provides bracket to secure Biscuit SBCs  
Size: 103.7 x 56 mm (4.08" x 2.2")

### Ordering Information

| P/N           | Description                            |
|---------------|--|
| PCM-110-00A3E | 1-slot PCI riser Card for Biscuit SBCs |



## PCM-261

### LVDS/TTL to DVI Module

Supports 18 and 24-bit LVDS to DVI  
Supports 18 or 24-bit TTL LCD to DVI (optional)

### Specifications

| General                      |  |
|------------------------------|--|
| Chipset                      | Silicon Image Sil 164; NS DS90CF364        |
| LCD Connector                | Hirose Output Connector; DVI               |
| Mechanical and Environmental |  |
| Dimensions (L x W)           | 72 x 62 mm                                 |
| Weight                       | 0.029 kg (0.064 lb)                        |
| Operating Temperature        | 0 ~ 60° C (32 ~ 140° F)                    |
| Operating Humidity           | 0% ~ 90% relative humidity, non-condensing |
| Power                        |  |
| Power Supply Voltage         | +5 V, ±5%                                  |

### Ordering Information

| Standard       |                           |
|----------------|---------------------------|
| PCM-261L-A0A1E | 24-bit LVDS to DVI Module |
| PCM-261L-B0A1E | 18-bit LVDS to DVI Module |
| PCM-261T-A0A1E | 24-bit TTL to DVI Module  |

### Packing List

|                   |
|-------------------|
| 1 x User manual   |
| 1 x PCM-261 board |