# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**PANDUIT**<sup>®</sup> building a smarter, unified business foundation Connect. Manage. Automate.

## **Product Bulletin**

### **Pan-Way<sup>®</sup> Pan-Pole<sup>™</sup>** Aluminum Outlet Poles for Power and Communication

Pan-Pole<sup>™</sup> Power and Communication Poles provide industry-leading solutions for cable routing in the open-office environment. These aluminum poles accept 70mm snap-on faceplates, as well as NEMA-standard screw-mount faceplates, and are provided with non-metallic 70mm (2.75") covers. Pan-Pole<sup>™</sup> Power Poles are supplied with a power entry box, including ½" and ¾" conduit breakouts and an 8" removable plate (not provided on communication-only poles). Options include having pre-terminated electrical outlets with divided channel for power and communication applications or having an open-channel communication pole. Both products are available in 11- and 13-foot lengths. Pan-Pole<sup>™</sup> Power Poles also have the option of extenders for custom configuration.



The dual-channel power and communication pole provides channel separation for the installation of communication cabling and modules, eliminating the need for two poles. One compartment is factory wired with two duplex style 20A, 125V NEMA 5-2OR grounding-type, specification-grade receptacles; leaving the second compartment for routing low-voltage cabling.

The single-channel communication-only pole allows for field installation of telephone, data network, or other low-voltage cabling.

#### Key Features Benefits

1" bend radius control	Cables will not exceed the minimum 1" bend radius requirement and degrade performance					
	Meets TIA/EIA standard and many warranty requirements					
Dual-channel aluminum construction	Provides complete separation of power and data, eliminating need for two poles					
Non-metallic cover	Tamper resistant yet allows access to installer for easy moves, adds, and changes; reduces cost to install and is easy to cut and modify					
Accepts Pan-Way® Snap-On Faceplates	Eliminates need for screw-on faceplates and allows for customized placement of data outlets					
UL5A/CSA listed	Meets the latest UL/CSA listing requirements					
Available in two colors	Coordinates with a variety of environments					
Optimized for use with Pan-Net® Connectivity System Network	Provides a complete network cabling solution					

#### **Technical Information**

Materials:	Aluminum base/PVC cover						
Compliance:	Material is RoHS (Restriction of Hazardous Substances) compliant						
Approvals:	UL & CSA rated to 600V						
Color:	International White (IW) or Electric Ivory (EI)						

#### Ordering Information

Part Description	Std. Pkg. Color	Qty.				
on Pole						
Power/communication pole.	Off White	1				
Power/communication pole.	Off White	1				
	· · · · · · · · · · · · · · · · · · ·					
Communication pole.						
Communication pole.	Off White	1				
S						
Extension kit to extend 11' power pole to 22'.	Off White	1				
Extension kit to extend 13' power pole to 16'.	Off White	1				
Standard Faceplate Bracket						
Power addition kit with 20A rectangular outlet.	Off White	1				
Power addition kit without 20A rectangular outlet.	Off White	1				
B-X Standard faceplate bracket.						
on Pole Replacement Parts						
Replacement kit.	Off White	1				
Replacement ceiling trim plate.	Off White	1				
Replacement end cap with floor grip pad.	Off White	1				
Replacement bend radius control ramp with T-bar bracket.	Gray	1				
	Dr Pole         Power/communication pole.         Power/communication pole.         Communication pole.         Communication pole.         Extension kit to extend 11' power pole to 22'.         Extension kit to extend 13' power pole to 16'.         Standard Faceplate Bracket         Power addition kit with 20A rectangular outlet.         Power addition kit without 20A rectangular outlet.         Standard faceplate bracket.         Don Pole Replacement Parts         Replacement kit.         Replacement ceiling trim plate.         Replacement end cap with floor grip pad.	Part Description       Color         on Pole       Power/communication pole.       Off White         Power/communication pole.       Off White         Communication pole.       Off White         Extension kit to extend 11' power pole to 22'.       Off White         Extension kit to extend 13' power pole to 16'.       Off White         Standard Faceplate Bracket       Power addition kit with 20A rectangular outlet.       Off White         Power addition kit with 20A rectangular outlet.       Off White       Standard faceplate bracket.         Gray       Off Pole Replacement Parts       Gray         Replacement kit.       Off White       Off White         Replacement ceiling trim plate.       Off White       Off White				

#### **Fill Capacity**

			Electrical Cables		Data Grade Cables							Audio/Video		Fiber Optic Cable	
Raceway Type and Configuration			14 AWG	12 AWG	10 AWG		24 /	AWG/U1	ГР СМ			RG6		2 Strand	
		Fill Area (n²)	THHN/T90		Cat. 5e – Plenum		Cat. 6		Cat. 6A						
			0.111	0.130	0.164	DIA. =	DIA. = 0.193 DIA. = 0.250		DIA. = 0.330		DIA. = 0.275		DIA. = 0.175		
			FILL		FILL		FILL		FILL		FILL		FILL		
			MAX	MAX	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX	SPEC	MAX
			(UL Te	mp Ris	e Test)	40%	60%	40%	60%	40%	60%	40%	60%	40%	60%
1a	Power and Communication: Snap-On Faceplates (Power)	0.47	**	11	**	**	**	**	**	**	**	3	4	7	11
1b	Power and Communication: Snap-On Faceplates (Communication)	2.75	**	**	**	37	56	22	33	12	19	18	27	45	68
2a	Power and Communication: Snap-On Faceplates (Power)	0.43	**	11	**	**	**	**	**	**	**	2	4	7	10
2b	Power and Communication: Snap-On Faceplates (Communication)	2.15	**	**	**	29	44	17	26	10	15	14	21	35	53
3	Communication-Only: Snap-On Faceplates	3.47	**	**	**	47	71	28	42	16	24	23	35	57	86
4	Communication-Only: Screw-On Faceplates	2.83	**	**	**	38	58	23	34	13	19	19	28	47	70

AWG dimensions represent typical outer cable diameter in inches.

#### **Related Products**



Pan-Pole<sup>™</sup> Power Pole Extension Kits

Pan-Pole<sup>™</sup> Power Pole Extension Kits include a fully assembled 11' or 3' power pole with dditional wing and

brace/coupler, and additional wing and screws. Customer needs to purchase separate 11' or 13' standard pole to configure a 22' or 16' pole length requirement.



Pan-Pole<sup>™</sup> Power Addition Kits and Standard Faceplate Brackets

Pan-Pole<sup>™</sup> Power Addition Kits (UL listed for field installation) provide for the addition of power outlets to the power and communication pole. This allows for the installation of up to three additional duplex outlets, for a total of five.

The Standard Faceplate Bracket (for data) is used to mount NEMA-standard, single-gang, screw-on communication faceplates (not for use with snap-on faceplates).



Pan-Pole<sup>™</sup> Power and Communication Pole Replacement Parts Kit

Pan-Pole<sup>™</sup> Power and Communication Pole Replacement Parts Kit includes

bend radius control ramp with two screws, T-bar brackets with one thumbscrew, one ceiling trim plate (two pieces), and one end cap with floor grip pad. Replacement ceiling trim plates, end caps with floor grip pads, and bend radius control ramp with T-bar bracket are also available individually.

PANDUIT CANADA Markham, Ontario cs-cdn@panduit.com Phone: 800.777.3300 PANDUIT EUROPE LTD. London, UK cs-emea@panduit.com Phone: 44.20.8601.7200

 TD.
 PANDUIT SINGAPORE PTE. LTD.

 Republic of Singapore
 cs-ap@panduit.com

 7200
 Phone: 65.6305.7575

PANDUIT JAPAN PA Tokyo, Japan Gu cs-japan@panduit.com cs Phone: 81.3.6863.6000 Ph

PANDUIT LATIN AMERICA Guadalajara, Mexico cs-la@panduit.com Phone: 52.33.3777.6000 PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia cs-aus@panduit.com Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

WORLDWIDE SUBSIDIARIES AND SALES OFFICES



For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300 and reference SRCB03 ©2011 Panduit Corp. ALL RIGHTS RESERVED. Product Bulletin Number **WW-SRCB03** 12/2011