



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





**10W LED Driver with 700mA Constant Current
PDA010B LED Power Supply for Indoor Lighting**



Features

- Constant Current
- OVP, OCP, Short/Open Circuit Protection
- IP20 Rating
- UL8750 Compliant
- SELV Compliant
- Brownout/Brownout Recovery
- Low Profile Design

Applications

- Indoor Lighting
- Architectural Lighting

Safety Approvals

- cUL/UL
- PSE

Mechanical Characteristics

- Length: 106mm (4.17in)
- Width: 40mm (1.57in)
- Height: 21mm (0.83in)
- Weight: 85g (3oz)

Output Specifications

Model	DC Output Voltage Range			Output Current Range			Max Power
	Min.	Typ.	Max.	Min.	Typ.	Max.	
PDA010B-700C	7.5V	-	12V	650mA	700mA	750mA	9W

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:

AC Input Voltage
90 to 132VAC

Nominal AC Input Voltage
100 to 127VAC

Leakage Current
0.5mA maximum at 110VAC

Maximum Input Current
≤160mA at 100VAC

OUTPUT:

Total Output Power
9W absolute maximum

Efficiency
70% minimum at full load, nominal AC input

Power Factor
≥0.95 at full load, nominal AC input

Ripple
<1A

Turn-on/off Delay Time
0.5ms maximum at nominal AC power on

ENVIRONMENTAL:

Operating Temperature -20 to +50°C
Storage Temperature -40 to +85°C

Operating Humidity 10 to 95%
Storage Humidity 05 to 95%

Warranty
3 Years

Ingression Protection
IP20

EMC

EN55015, FCC 47 Part 15, EN55022 Class B

Immunity

IEC61000-4-2
IEC61000-4-5
IEC61000-3-2 Class C
IEC61000-3-3

Isolation Test (HI-POT)

Primary to secondary: 3750VAC for 1 minute, 10mA

Insulation Resistance

Primary to secondary: >5M OHM 500VDC, 1 minute

FEATURES:

Input Over Current Protection

The input power line will be fused with a 1.6A fuse

Short Circuit Protection

The Driver will withstand a short circuit across the outputs without damage

Output Over Voltage Protection

The output shall be protected (latched) from over voltage

Open Circuit Protection

Once the circuit is opened, the output voltage should be less than 14.4V at nominal AC input conditions.

Lifetime

20K Hours minimum

Input / Output Connection

2-pin terminal block

Input / Output Wires (Solid or Stranded)

Position	Terminal Color	Specification
Line	Brown	AWG10~24
Neutral	Blue	AWG10~24
Vout+	Red	AWG10~24
Vout-	Black	AWG10~24

