



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





15W Constant Current LED Driver PDA015B Power Supply for Indoor Lighting



Features

- UL8750 Compliant
- IP20 Rated
- Constant Current
- Brownout/Brownout Recovery
- SELV Compliant
- OVP, OCP, Short/Open Circuit Protection
- Power Factor Correction
- Wide Temperature Range

Applications

- Indoor Lighting
- Architectural Lighting

Safety Approvals

- cUL/UL
- PSE

Mechanical Characteristics

- Length: 132mm (5.2in)
- Width: 40mm (1.6in)
- Height: 21mm (0.8in)
- Weight: 120g (4.2oz)

Output Specifications

Model	DC Output Voltage Range			Output Current Range			Max Power
	Min.	Typ.	Max.	Min.	Typ.	Max.	
PDA015B-350C	17.5V	-	42V	300mA	350mA	400mA	16.8W

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:

AC Input Voltage
90 to 132VAC

Nominal AC Input Voltage
100 to 127VAC

Leakage Current
0.5mA maximum

Maximum Input Current
≤0.3A at 100VAC

AC Inrush Current
≤20A at 120VAC, full load

OUTPUT:
Total Output Power
16.8W maximum

Efficiency
82% minimum

Power Factor
≥0.9 at full load, nominal AC input

Ripple
<1A

ENVIRONMENTAL:

Operating Temperature -20 to +50°C
Storage Temperature -40 to +85°C

Operating Humidity 10 to 95%
Storage Humidity 05 to 95%

Warranty
3 Years

Lifetime
20K hours minimum

EMC

EN55015, FCC 47 Part 18, EN55022 Class B

Immunity

IEC61000-4-2
IEC61000-4-5
IEC61000-3-2 Class C
IEC61000-3-3

Isolation Test

Primary to secondary: 3230VAC for 1 minute, 10mA

Insulation Resistance

Primary to secondary: >5M OHM 500VDC, 1 minute

FEATURES:

Input Current Protection

The input power line is fused with a 1.6A fuse

Short Circuit

Driver will withstand short circuit across outputs without damage

Output Overvoltage Protection

Output is protected (latched) from over voltage

Open Circuit Protection

If circuit is open, output will not be damaged at nominal AC input conditions

Input / Output Connection

2-pin terminal block

Input / Output Wires (Solid or Stranded)

Position	Terminal Color	Specification
Line	Brown	AWG16~18
Neutral	Blue	AWG16~18
Vout+	Red	AWG16~18
Vout-	Black	AWG16~18

Ingression Protection

IP20

Dimension Diagram Unit:mm

