



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!





Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





DESCRIPTION

The **PDB-C607-2** is a silicon red enhanced solderable photodiode designed for low capacitance and high speed for photoconductive applications

FEATURES

- Red Enhanced
- Photoconductive
- High Quantum Efficiency

RELIABILITY

Contact Luna for recommendations on specific test conditions and procedures.

APPLICATIONS

- Optical Encoders
- Position Sensor
- Industrial Controls
- Instrumentation



ABSOLUTE MAXIMUM RATINGS

| SYMBOL | MIN | | MAX | UNITS | |
|------------------------|-----|----|------|-------|----------------------------------------------|
| Reverse Voltage | - | - | 75 | V | T _a = 23°C UNLESS OTHERWISE NOTED |
| Storage Temperature | -40 | - | +125 | °C | - |
| Operating Temperature | -40 | to | +100 | °C | - |
| Soldering Temperature* | - | - | +224 | °C | - |

* 1/16 inch from case for 3 seconds max.

OPTO-ELECTRICAL PARAMETERS

T_a = 23°C UNLESS NOTED OTHERWISE

| PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNITS |
|----------------------------|--------------------------------|-----|---------------------|------|-------|
| Short Circuit Current | H= 100 fc, 2850 K | 165 | 185 | - | μA |
| Dark Current | V _R = 5 V | - | 2 | 35 | nA |
| Shunt Resistance | V _R = 10 mV | 6 | 100 | - | MΩ |
| Junction Capacitance | V _R =5V; f = 1 MHz | - | 125 | - | pF |
| Spectral Application Range | Spot Scan | 350 | - | 1100 | nm |
| Breakdown Voltage | I=10 μA | 50 | 100 | - | V |
| Noise Equivalent Power | V _R =0V@λ= Peak | - | 5x10 ⁻¹⁴ | - | W/√Hz |
| Response Time** | RL = 1KΩ, V _R = 5 V | - | 25 | - | nS |

**Response time of 10% to 90% is specified at 660nm wavelength light.

TYPICAL PERFORMANCE

SPECTRAL RESPONSE

