



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SERIES: PDS1-S | DESCRIPTION: DC-DC CONVERTER
FEATURES


- 1 W isolated output
- smaller package
- single unregulated output
- 1,500 Vdc isolation
- short circuit protection
- extended temperature range (-40~105°C)
- antistatic protection up to 8kV
- UL 60950-1 approval
- high efficiency at light load
- efficiency up to 82%



| MODEL | input voltage | | output voltage (Vdc) | output current | | output power max (W) | ripple and noise ² typ (mVp-p) | efficiency typ (%) |
|-----------------------------|---------------|-------------|-------------------------|----------------|----------|-------------------------|--|-----------------------|
| | typ (Vdc) | range (Vdc) | | min (mA) | max (mA) | | | |
| PDS1-S3-S3-S | 3.3 | 2.97~3.63 | 3.3 | 30 | 303 | 1 | 30 | 75 |
| PDS1-S3-S5-S ¹ | 3.3 | 2.97~3.63 | 5 | 20 | 200 | 1 | 30 | 80 |
| PDS1-S5-S3-S | 5 | 4.5~5.5 | 3.3 | 30 | 303 | 1 | 30 | 76 |
| PDS1-S5-S5-S ¹ | 5 | 4.5~5.5 | 5 | 20 | 200 | 1 | 30 | 80 |
| PDS1-S5-S9-S ¹ | 5 | 4.5~5.5 | 9 | 12 | 111 | 1 | 30 | 80 |
| PDS1-S5-S12-S ¹ | 5 | 4.5~5.5 | 12 | 9 | 84 | 1 | 30 | 81 |
| PDS1-S5-S15-S ¹ | 5 | 4.5~5.5 | 15 | 7 | 67 | 1 | 60 | 81 |
| PDS1-S5-S24-S ¹ | 5 | 4.5~5.5 | 24 | 4 | 42 | 1 | 60 | 81 |
| PDS1-S12-S3-S | 12 | 10.8~13.2 | 3.3 | 30 | 303 | 1 | 30 | 76 |
| PDS1-S12-S5-S ¹ | 12 | 10.8~13.2 | 5 | 20 | 200 | 1 | 30 | 80 |
| PDS1-S12-S9-S ¹ | 12 | 10.8~13.2 | 9 | 12 | 111 | 1 | 30 | 80 |
| PDS1-S12-S12-S ¹ | 12 | 10.8~13.2 | 12 | 9 | 83 | 1 | 30 | 81 |
| PDS1-S12-S15-S ¹ | 12 | 10.8~13.2 | 15 | 7 | 67 | 1 | 60 | 80 |
| PDS1-S15-S5-S | 15 | 13.5~16.5 | 5 | 20 | 200 | 1 | 30 | 80 |
| PDS1-S15-S12-S | 15 | 13.5~16.5 | 12 | 9 | 83 | 1 | 60 | 80 |
| PDS1-S15-S15-S | 15 | 13.5~16.5 | 15 | 7 | 67 | 1 | 60 | 81 |
| PDS1-S24-S3-S | 24 | 21.6~26.4 | 3.3 | 30 | 303 | 1 | 30 | 76 |
| PDS1-S24-S5-S ¹ | 24 | 21.6~26.4 | 5 | 20 | 200 | 1 | 30 | 80 |
| PDS1-S24-S9-S ¹ | 24 | 21.6~26.4 | 9 | 12 | 111 | 1 | 30 | 80 |
| PDS1-S24-S12-S ¹ | 24 | 21.6~26.4 | 12 | 9 | 84 | 1 | 30 | 81 |
| PDS1-S24-S15-S ¹ | 24 | 21.6~26.4 | 15 | 7 | 67 | 1 | 60 | 82 |
| PDS1-S24-S24-S ¹ | 24 | 21.6~26.4 | 24 | 4 | 42 | 1 | 60 | 82 |

Notes: 1. UL approved
2. Ripple and noise are measured at 20 MHz BW by "parallel cable" method with 1 μ F ceramic and 10 μ F electrolytic capacitors on the output.

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|-------------------------|-------------------------|------|-----|------|-------|
| operating input voltage | 3.3 Vdc input models | 2.97 | 3.3 | 3.63 | Vdc |
| | 5 Vdc input models | 4.5 | 5 | 5.5 | Vdc |
| | 12 Vdc input models | 10.8 | 12 | 13.2 | Vdc |
| | 15 Vdc input models | 13.5 | 15 | 16.5 | Vdc |
| | 24 Vdc input models | 21.6 | 24 | 26.4 | Vdc |
| surge voltage | for maximum of 1 second | | | | |
| | 3.3 Vdc input models | -0.7 | | 5 | Vdc |
| | 5 Vdc input models | -0.7 | | 9 | Vdc |
| | 12 Vdc input models | -0.7 | | 18 | Vdc |
| | 15 Vdc input models | -0.7 | | 21 | Vdc |
| | 24 Vdc input models | -0.7 | | 30 | Vdc |
| filter | capacitance filter | | | | |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|-------------------------|-------------------------------------|-----|-----|-------|-------|
| line regulation | for Vin change of 1% | | | | |
| | 3.3 Vdc output models | | | ±1.5 | % |
| | all other models | | | ±1.2 | % |
| load regulation | measured from 10% load to full load | | | | |
| | 3.3 Vdc output models | | 18 | | % |
| | 5 Vdc output models | | 12 | | % |
| | 9 Vdc output models | | 8 | | % |
| | 12 Vdc output models | | 7 | | % |
| | 15 Vdc output models | | 6 | | % |
| | 24 Vdc output models | | 5 | | % |
| voltage accuracy | see tolerance envelope curve | | | | |
| switching frequency | 100% load, nominal input voltage | | 100 | 300 | kHz |
| temperature coefficient | 100% load | | | ±0.03 | %/°C |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|------------------------|-----|-----|-----|-------|
| short circuit protection | automatic recovery | | | | |

SAFETY AND COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|-------------------------------|--|-----------|-----|-----|-------|
| isolation voltage | input to output for 1 minute at 1 mA max. | 1,500 | | | Vdc |
| isolation resistance | input to output at 500 Vdc | 1,000 | | | MΩ |
| safety approvals ¹ | UL 60950-1 | | | | |
| conducted emissions | CISPR22/EN55022, class B (external circuit required, see Figure 1) | | | | |
| radiated emissions | CISPR22/EN55022, class B (external circuit required, see Figure 1) | | | | |
| ESD | IEC/EN61000-4-2, class B, contact ±8kV | | | | |
| MTBF | as per MIL-HDBK-217F @ 25°C | 3,500,000 | | | hours |
| RoHS | 2011/65/EU | | | | |


Note: 1. See specific models noted on page 1

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|-------------------------|-----|-----|-----|-------|
| operating temperature | see derating curve | -40 | | 105 | °C |
| storage temperature | | -55 | | 125 | °C |
| storage humidity | non-condensing | | | 95 | % |
| temperature rise | at full load, Ta = 25°C | | 25 | | °C |

SOLDERABILITY

| parameter | conditions/description | min | typ | max | units |
|----------------|---------------------------------|-----|-----|-----|-------|
| hand soldering | 1.5 mm from case for 10 seconds | | | 300 | °C |
| wave soldering | see wave soldering profile | | | 260 | °C |






MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|---------------|---|-----|-----|-----|-------|
| dimensions | 11.60 x 6.00 x 10.10 (0.457 x 0.236 x 0.398 inch) | | | | mm |
| case material | plastic (UL94-V0) | | | | |
| weight | | | 1.2 | | g |



MECHANICAL DRAWING

units: mm[inch]
 tolerance: $\pm 0.25[\pm 0.010]$
 pin section tolerance: $\pm 0.10[\pm 0.004]$

| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | GND |
| 2 | Vin |
| 3 | 0V |
| 4 | +Vo |



DERATING CURVES



EMC RECOMMENDED CIRCUIT

Figure 1




Table 1

| Recommended external circuit components | | |
|---|-----------------|-------------|
| V_{in} (Vdc) | C_0 | L_{DM} |
| 3.3 | 4.7 μ F/50V | 6.8 μ H |
| 5 | 4.7 μ F/50V | 6.8 μ H |
| 12 | 4.7 μ F/50V | 6.8 μ H |
| 15 | 4.7 μ F/50V | 6.8 μ H |
| 24 | 4.7 μ F/50V | 6.8 μ H |

TEST CONFIGURATION

Figure 2




Table 2

| External components | |
|---------------------|--|
| L_{in} | 4.7 μ H |
| C_{in} | 220 μ F, ESR < 1.0 Ω at 100 kHz |

Note: Input reflected-ripple current is measured with an inductor L_{in} and Capacitor C_{in} to simulate source impedance.

APPLICATION NOTES

1. Output load requirement

To ensure this module can operate efficiently and reliably, the minimum output load may not be less than 10% of the full load during operation. If the actual output power is low, connect a resistor at the output end in parallel to increase the load.

2. Overload Protection

Under normal operating conditions, the output circuit of this product has no protection against overload. The simplest method to add this is to add a circuit breaker to the circuit.

3. Recommended circuit

This series has been tested according to the following recommended testing circuit before leaving the factory. This series should be tested under load (see Figure 3 & Table 3). If you want to further decrease the input/output ripple, you can increase the capacitance accordingly or choose capacitors with low ESR. However, the capacitance of the output filter capacitor must be appropriate. If the capacitance is too high, a startup problem might arise. For every channel of the output, to ensure safe and reliable operation, the maximum capacitance must be less than the maximum capacitive load (see Table 4).

Figure 3




Table 3

| Vin (Vdc) | Cin (μF) | Vo (Vdc) | Cout (μF) |
|-----------|----------|----------|-----------|
| 3.3 | 4.7 | 3.3 | 10 |
| 5 | 4.7 | 5 | 10 |
| 12 | 2.2 | 9 | 4.7 |
| 15 | 1 | 12 | 2.2 |
| 24 | 1 | 15 | 1 |
| -- | -- | 24 | 0.47 |

Table 4

| Vout (Vdc) | Max. Capacitive Load (μF) |
|------------|---------------------------|
| 3.3 | 220 |
| 5 | 220 |
| 9 | 220 |
| 12 | 220 |
| 15 | 220 |
| 24 | 220 |

Note: It's not recommended to connect any external capacitors in applications with less than 0.5 watt output.

- Note:
1. Operation under minimum load will not damage the converter; however, they may not meet all specifications listed.
 2. Max. capacitive load tested at input voltage range and full load.
 3. It is recommended to use either ceramic capacitors or electrolytic capacitors on the input and the output. Using tantalum capacitors may increase the risk of failure.
 4. All specifications measured at: Ta=25°C, humidity<75%, nominal input voltage and rated output load, unless otherwise specified.

REVISION HISTORY

| rev. | description | date |
|------|---|------------|
| 1.0 | initial release | 03/19/2013 |
| 1.01 | added model PDS1-S15-S12-S | 07/29/2013 |
| 1.02 | added model PDS1-S12-S3-S, updated spec | 03/07/2014 |
| 1.03 | added UL approval to some models | 10/28/2014 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC[®]

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.